

### Materials

Pin (outer sleeve) : Brass, machined, CuZn38Pb2  
Clip (contact 4 finger) : Beryllium copper, heat treated or PHBZ  
Plating (outer sleeve) : Tin plated : 2µm/80µ"nickel, 5µm/200µ" Tin  
Plating clip (contact): 2µm/80µ"nickel, full gold  
Insulator body (black) : Glass filled thermoplastic polyester UL94V-0

### Electrical





Current rating : 3 Amps/contact max.  
Contact resistance : Max 4mΩ  
Insulation resistance : Min 10,000mΩ @ 500 V AC  
Operating Voltage : 100 VRMS / 150 V AC

### Mechanical

Operating temperature : Tin plated: -40°C to +105°C  
Average insertion force with steel pin of: 0.43mm/0.017" <250g  
Average withdrawal force with steel pin of: 0.43mm/0.017" >50g  
Mechanical life : min.200

\*7 = Spacing 7.62MM

Packaging: Tube



P.C.B. LAYOUT

**RoHS**  
Compliant

ITEM NO

**AR24-HZL- \*7-TT-R**

TITLE IC-Socket, 24Pin, Machined Contacts,  
Pitch: 2.54MM, Pin Length: 7.43MM

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
© Copyright 2009 by Assmann Electronic Components  
All International Rights Reserved

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [IC & Component Sockets](#) category:*

*Click to view products by [Assmann](#) manufacturer:*

Other Similar products are found below :

[714-43-102-31-012000](#) [0066-3-17-15-30-14-02-0](#) [0134-0-15-15-32-27-04-0](#) [614-DG5](#) [6527-0-00-15-00-00-03-0](#) [670](#) [672](#) [673](#) [712-93-120-41-001000](#) [714-93-104-31-018000](#) [8059-4G1-LF](#) [807-22-001-10-001101](#) [807-22-001-10-003101](#) [807-22-001-10-004101](#) [807-22-001-10-006101](#) [807-22-001-30-011101](#) [807-22-001-30-012101](#) [807-22-001-30-013101](#) [807-22-001-30-014101](#) [8-1437531-4](#) [8150-6P10](#) [833-93-034-10-001000](#) [835-43-014-10-001000](#) [851-41-006-10-001000](#) [851-43-008-20-001000](#) [851-43-014-20-001000](#) [851-93-006-20-001000](#) [851-93-010-20-001000](#) [852-10-026-10-001000](#) [853-43-020-10-001000](#) [86.010.0053.0](#) [116-43-306-41-003000](#) [116-43-308-41-007000](#) [116-87-308-41-007101](#) [PX-68LCC](#) [PX-84LCC](#) [121-13-318-41-001000](#) [121-13-320-41-001000](#) [121-13-308-41-001000](#) [123-43-314-41-801000](#) [123-43-420-41-001000](#) [123-43-636-41-001000](#) [123-87-320-41-001101](#) [122-13-316-41-001000](#) [123-13-624-41-001000](#) [123-43-306-41-001000](#) [123-43-322-41-801000](#) [123-43-428-41-001000](#) [123-43-624-41-001000](#) [12-3513-11](#)