TECHNICAL SPECIFICATIONS

D-Sub Hood:

Material: Zinc, Nickel Plated -40°C to +120°C Operating Temperature:

Cable Entry: Top Entry

Thumbscrews: UNC 4-40 (Standard)

Cable O.D: Up to 11,5mm (Size 9-37)

Up to 17mm (Size 50)

D-Sub High Density:

Insulator: PBT, Black, UL94 V-0

Shell: Stamped Steel, Tin Plated

Contact pins: Copper Alloy

Stamped & Formed pins: 100 inserts min

Contacts Plating: Selective Gold over Nickel

Operating Temperature: -55°C to +105°C Withstanding voltage: 500V for 1 minute

500MΩ min Insulator resistance:



D-Su	b-H	looc
------	-----	------

<u> </u>	C
Dim B	Dim C
39,5	15,0
41,5	15,0

Features:

- Available in sizes 9-15-25-37
- Packed in Kit with FEMALE/MALE HD-connector
- Re-openable
- Full Metal Jackscrew as standard.

Size DTZK	Dim A	Dim B	Dim C
9-way	31,0	39,5	15,0
15-way	39,5	41,5	15,0
25-way	53,5	48,5	15,0
37-way	71,0	53,0	15,0
50-way			

Ordering information:

Size:	P/N - Kitted:	Product Code - MALE Conn. Kit
HD 15	6355-0012-01	DTZK09-HDP15-K
HD 26	6355-0012-02	DTZK15-HDP26-K
HD 44	6355-0012-03	DTZK25-HDP44-K
HD 62	6355-0012-04	DTZK37-HDP62-K
HD 78	6355-0012-05	DTZK50-HDP78-K

D-Sub Connector Kits (100 inserts min.)

	Size:	P/N - Kitted:	Product Code - FEMALE Conn. Kit
	HD 15	6355-0012-11	DTZK09-HDS15-K
	HD 26	6355-0012-12	DTZK15-HDS26-K
	HD 44	6355-0012-13	DTZK25-HDS44-K
Ī	HD 62	6355-0012-14	DTZK37-HDS62-K
	HD 78	6355-0012-15	DTZK50-HDS78-K

Rörkullsvägen 4

SE-302 41 HALMSTAD, Sweden

Tel.: +46-(0)35-15 13 90 Fax: +46-(0)35-15 13 99

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Encitech manufacturer:

Other Similar products are found below:

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X