


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>H07RN-F</b>	29.11.2013

Heavy standard construction

For mechanically more demanding applications

1000 V AC @ protected + static laying

Arrangements made of single-core, rubber-sheathed cables H07RN-F can be used for short circuit-proof and short-to-ground-proof installations in accordance with VDE 0100 Part 520



Cold-resistant



Mechanical resistance



Oil-resistant



UV-resistant

#### Info

Medium mechanical stress

Oil-resistant

#### Application range

Handheld and power supply devices according to HD 516

Medium, mechanical stress (H07RN-F)/ industrial, agricultural use

Dry or damp rooms as well as outdoors (taking into account all normative power characteristics) according to HD 516/VDE 0298-300

#### Design

Bare copper wire according to HAR

Core insulation: rubber compound type EI 4

Outer sheath: rubber compound, type EM2

#### Norm references / Approvals


<HAR> H07RN-F cable type approval according to EN 50525-2-21

#### Product features

Flame-retardant according IEC 60332-1-2

Oil-resistant according to EN 60811-404

Product Management	Document: LAPP_PRO52EN.pdf	1 / 4
--------------------	----------------------------	-------

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>H07RN-F</b>	<b>29.11.2013</b>

### Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil  $\leq$  30 kg or  $\leq$  250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

\*OD = Outer diameter

### Technical Data

Core identification code:	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	4 to 8 xOD* (HD 516)
Nominal voltage:	U <sub>0</sub> /U: 450/750 V
Test voltage:	2500 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Current rating:	According to IEC 60364-5-52/ VDE 0298-4 HD 516/VDE 0298-300
Temperature range:	-25°C to +60°C

Product Management	Document: LAPP_PRO52EN.pdf	2 / 4
--------------------	----------------------------	-------

Part number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)
1600096	1 X 1,5	5,7 - 7,1	14.4
1600099	1 X 2,5	6,3 - 7,9	24.0
1600097	1 X 4	7,2 - 9	38.4
1600098	1 X 6	7,9 - 9,8	57.6
1600194	1 X 10	9,5 - 11,9	96.0
1600195	1 X 16	10,8 - 13,4	153.6
1600196	1 X 25	12,7 - 15,8	240.0
1600193	1 X 35	14,3 - 17,9	336.0
1600197	1 X 50	16,5 - 20,6	480.0
1600189	1 X 70	18,6 - 23,3	672.0
1600190	1 X 95	20,8 - 26	912.0
1600198	1 X 120	22,8 - 28,6	1152.0
1600191	1 X 150	25,2 - 31,4	1440.0
1600175	1 X 185	27,6 - 34,4	1776.0
1600177	1 X 240	30,6 - 38,3	2304.0
30015435	1 X 300	33,5 - 41,9	2880.0
1600117	3 G 1,0	8,3 - 10,7	28.8
1600199	2 X 1,5	8,5 - 11	28.8
1600103	3 G 1,5	9,2 - 11,9	43.2
16001233	4 G 1,5	10,2 - 13,1	57.6
16001043	5 G 1,5	11,2 - 14,4	72.0
1600151	7 G 1,5	14 - 17,5	100.8
1600148	12 G 1,5	17,6 - 22,4	172.8
1600259	19 G 1,5	20,7 - 26,3	273.6
1600166	24 G 1,5	24,3 - 30,7	345.6
1600263	25 G 1,5	25,1 - 25,9	360.0
1600187	2 X 2,5	10,2 - 13,1	48.0
1600118	3 G 2,5	10,9 - 14	72.0
16001053	4 G 2,5	12,1 - 15,5	96.0
16001293	5 G 2,5	13,3 - 17	120.0
1600152	7 G 2,5	16,5 - 20	168.0
1600154	12 G 2,5	20,6 - 26,2	288.0
1600156	19 G 2,5	25,5 - 31	456.0
1600157	24 G 2,5	28,8 - 36,4	576.0

Part number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)
1600186	2 X 4	11,8 - 15,1	76.8
1600119	3 G 4	12,7 - 16,2	115.2
16001063	4 G 4	14 - 17,9	153.6
16001303	5 G 4	15,6 - 19,9	192.0
1600161	7 G 4	21 - 21,8	268.8
1600120	3 G 6	14,1 - 18	172.8
16001073	4 G 6	15,7 - 20	230.4
16001313	5 G 6	17,5 - 22,2	288.0
1600121	3 G 10	19,1 - 24,2	288.0
16001083	4 G 10	20,9 - 26,5	384.0
16001093	5 G 10	22,9 - 29,1	480.0
1600122	3 G 16	21,8 - 27,6	460.8
16001103	4 G 16	23,8 - 30,1	614.4
16001113	5 G 16	26,4 - 33,3	768.0
16001123	4 G 25	28,9 - 36,6	960.0
16001133	5 G 25	32 - 40,4	1200.0
1600124	3 G 35	29,3 - 37,1	1008.0
16001143	4 G 35	32,5 - 41,1	1344.0
16001363	5 G 35	37 - 45	1680.0
16001153	4 G 50	37,7 - 47,5	1920.0
1600126	5 G 50	40 - 50,8	2400.0
16001163	4 G 70	42,7 - 54	2688.0
16001283	4 G 95	48,4 - 61	3648.0
16001323	4 G 120	53 - 66	4608.0
16000883	4 G 150	58 - 73	5760.0
1600141	4 G 185	64 - 80	7104.0
1600183	4 G 240	72 - 91	9216.0

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [AC Power Leads](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[1300000159](#) [1300030004](#) [1300000017](#) [1300000113](#) [6483](#) [70-841-030](#) [1300030156](#) [1300010059](#) [1300000197](#) [1300010120](#) [1300000110](#)  
[1300010103](#) [1300000160](#) [1300000018](#) [1300030127](#) [1300000026](#) [1300000136](#) [1300000146](#) [1300000071](#) [1300030131](#) [1300000027](#)  
[1300000166](#) [1300000235](#) [1300000167](#) [1300010011](#) [1300000168](#) [1300010029](#) [1300000169](#) [1300010095](#) [1300000222](#) [1300010030](#)  
[PC20C13BL8.2](#) [PC20C13BL8.2-X](#) [07199-SP024](#) [PC14C13RD10-Q](#) [PC14C13YL10-Q](#) [LPCA16X](#) [LPCA21X](#) [NPCA16X](#) [NPCA21X](#)  
[LPCA17X](#) [LPCA22X](#) [NPCA17X](#) [NPCA22X](#) [LPCA18X](#) [LPCA23X](#) [NPCA18X](#) [NPCA23X](#) [NPCA19X](#) [NPCA24X](#)