


U.I. Lapp GmbH	PRODUCT INFORMATION	
	H05RN-F	29.11.2013

Rubber cable for handheld devices and chains of decorative lights

Type-compliant versions <HAR>-certified with "<HAR>" testing and certification mark for accelerated granting of approvals if final application of cable is within the European GENELEC area



Cold-resistant



Oil-resistant



UV-resistant

Info

Oil-resistant

Application range

According to HD 516/VDE 0298-300: for supplying devices in households, kitchens or offices under light mechanical stress; handheld inspection lamps

According to HD 516/VDE 0298-300: provided the maximum conductor temperature of +60 °C, the maximum outer sheath surface temperature of +50 °C and the lack of ozone resistance are taken into account, suitable for permanent use outdoors with conventional mechanical stress

Design

Bare copper wire according to HAR

Core insulation: rubber compound type EI 4

Outer sheath: rubber compound, type EM2

Norm references / Approvals

<HAR> cable type certified acc. EN 50525-2-21

Product features

Flame-retardant according IEC 60332-1-2

Oil-resistant according to EN 60811-404

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths


Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

*OD = Outer diameter

Product Management	Document: LAPP_PRO51EN.pdf	1 / 3
--------------------	----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	H05RN-F	29.11.2013

Technical Data

Core identification code:	Coloured according to HD 308
Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	4 to 8 xOD* (HD 516)
Nominal voltage:	U ₀ /U: 300/500 V
Test voltage:	2000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Current rating:	According to IEC 60364-5-52/ VDE 0298-4 HD 516/VDE 0298-300
Temperature range:	Flexible use: -25°C to +60°C

Product Management	Document: LAPP_PRO51EN.pdf	2 / 3
--------------------	----------------------------	-------

Part number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)
1600250	2 X 0,75	5,7 - 7,4	14.4
1600252	3 G 0,75	6,2 - 8,1	21.6
16002583	4 G 0,75	6,8 - 8,8	28.8
1600251	2 X 1,0	6,1 - 8	19.2
1600253	3 G 1,0	6,5 - 8,5	28.8

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC Power Leads](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[1300000159](#) [1300030004](#) [1300000017](#) [1300000113](#) [6483](#) [70-841-030](#) [1300030156](#) [1300010059](#) [1300000197](#) [1300010120](#) [1300000110](#)
[1300010103](#) [1300000160](#) [1300000018](#) [1300030127](#) [1300000026](#) [1300000136](#) [1300000146](#) [1300000071](#) [1300030131](#) [1300000027](#)
[1300000166](#) [1300000235](#) [1300000167](#) [1300010011](#) [1300000168](#) [1300010029](#) [1300000169](#) [1300010095](#) [1300000222](#) [1300010030](#)
[PC20C13BL8.2](#) [PC20C13BL8.2-X](#) [07199-SP024](#) [PC14C13RD10-Q](#) [PC14C13YL10-Q](#) [LPCA16X](#) [LPCA21X](#) [NPCA16X](#) [NPCA21X](#)
[LPCA17X](#) [LPCA22X](#) [NPCA17X](#) [NPCA22X](#) [LPCA18X](#) [LPCA23X](#) [NPCA18X](#) [NPCA23X](#) [NPCA19X](#) [NPCA24X](#)