














| | | |
|-------------------------------------|--------------------|--|
| U.I. Lapp GmbH | <h1>DATASHEET</h1> |  |
| EPIC KIT LS1 D6 8-POL FEMALE | | 75009694 29.11.2013 |

Circular connectors for servomotors and power supply
 High power at smallest installation space, Optimal solution for electric motors
 EMC-optimised
 Safety use in field environment by high protection class



-  Good chemical resistance
-  Corrosion-resistant
-  Industrial machinery and plant engineering
-  Maximum vibration protection
-  Mechanical resistance
-  Assembly time
-  Optimum strain relief
-  Space requirement
-  Robust
-  Integrated SKINTOP® cable gland
-  Waterproof
-  Wind Energy
-  Variety of approval certifications

| | | |
|--------------------|--|-------|
| Product Management | Document: EPIC KIT LS1 D6 8-POL FEMALE | 1 / 3 |
|--------------------|--|-------|

| | | |
|-------------------|-------------------------------------|--|
| U.I. Lapp GmbH | DATASHEET |  |
| | EPIC KIT LS1 D6 8-POL FEMALE | 75009694 29.11.2013 |

Application range

Plant engineering
Servo drives and servo assemblies

Remark


Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

| | |
|--------------------------------|---|
| Article number: | 75009694 |
| Rated voltage (V): | 630 V (2 mm contacts) 250 V (1 mm contacts) |
| Rated impulse voltage: | 6 kV (2 mm contacts) 4 kV (1 mm contacts) |
| Rated current (A): | 26A/3+PE+4, 25A/5+PE (2mm contacts) 7 A (1 mm contacts) |
| Contact resistance: | < 4 mOhm |
| Contacts: | Gold-plated brass |
| Number of contacts: | 3 + PE + 4 5 + PE |
| Termination methods: | Crimp termination: 0.5 - 4.0 mm ² (2 mm contacts) Crimp termination: 0.14 - 1.0 mm ² (1 mm contacts) |
| Material: | Housing: nickel-plated zinc die-casting, nickel-plated brass Insert: PA, Seal: FPM |
| Protection rating: | IP68 (10h / 1m) |
| Cycle of mechanical operation: | 500 |
| Temperature range: | -25°C až +125°C |
| VDE-tested: | Certified production control: VDE-REG. no. B25 |
| Degree of soiling: | 3 |

| | | |
|--------------------|--|-------|
| Product Management | Document: EPIC KIT LS1 D6 8-POL FEMALE | 2 / 3 |
|--------------------|--|-------|

| | | |
|-------------------|-------------------------------------|--|
| U.I. Lapp GmbH | <h1>DATASHEET</h1> |  LAPP GROUP |
| | EPIC KIT LS1 D6 8-POL FEMALE | 75009694 29.11.2013 |



| | | |
|--------------------|--|-------|
| Product Management | Document: EPIC KIT LS1 D6 8-POL FEMALE | 3 / 3 |
|--------------------|--|-------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular MIL Spec Connector](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)