

BKT, BKS SERIES

(1,00 mm) .0394"

POLARIZED MICRO HEADER & SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?BKT or www.samtec.com?BKS

Insulator Material: Liquid Crystal Polymer
Terminal Material: Phosphor Bronze
Plating: Au or Sn over 50µ" (1,27 µm) Ni
Current Rating: 2.8 A per pin (1 pin powered per row)
Operating Temp Range: -55°C to +125°C
Contact Resistance: 15 mΩ
Insertion Depth: (1,40 mm) .055" minimum
Insertion Force: (Single contact only) 1.5 oz (0,42 N) average
Normal Force: 40 grams (0,39 N) average
Withdrawal Force: (Single contact only) .75 oz (0,20 N) average
Max Cycles: 100 with 10µ" (0,25 µm) Au
RoHS Compliant: Yes


Processing:
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,10 mm) .004" max

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



APPLICATIONS



BKT LEAD STYLE	MATED HEIGHT*
-01	(4,14) .163
-02	(4,50) .177
-03	(5,00) .197
-04	(6,00) .236
-05	(7,00) .276

*Processing conditions will affect mated height.



Note: Some sizes, styles and options are non-standard, non-returnable.

BKT - **1** NO. OF POSITIONS

Mates with: **BKS**

07 thru 69
(Odd lead counts only)

-A OPTION

BODY STYLE - Specify **BODY STYLE** from chart

BODY STYLE	A	B	BOARD SPACE (Mated with BKS)
-01	(1,93) .076	(3,91) .154	(4,14) .163
-02	(2,29) .090	(4,27) .168	(4,50) .177
-03	(2,79) .110	(4,78) .188	(5,00) .197
-04	(3,78) .149	(5,77) .227	(6,00) .236
-05	(4,80) .189	(6,78) .267	(7,00) .276

-P OPTION

PLATING OPTION - **V**

-F = Gold flash on post, Matte Tin on tail

-L = 10µ" (0,25 µm) Gold on post, Matte Tin on tail

-S OPTION

OPTIONS

-S = Shrouded (15 positions minimum)

-A = Alignment Pin (Metal or plastic at Samtec discretion) (13 positions minimum)

-P = Pick & Place Pad (13 positions minimum)

-TR = Tape & Reel Packaging

BKS - **1** NO. OF POSITIONS

Mates with: **BKT**

07 thru 69
(Odd lead counts only)
(07 positions available with -TR only)

-P OPTION

-A OPTION

PLATING OPTION - **V**

-F = Pre-plated Gold flash on contact, Matte Tin on tail

-L = Pre-plated 10µ" (0,25 µm) Gold contact, Matte Tin on tail

OPTIONS

-A = Alignment Pin (Metal or plastic at Samtec discretion) (11 positions minimum)

-P = Pick and Place Pad (13 positions minimum)
Not always necessary for auto placement.

-TR = Tape & Reel Packaging

Due to technical progress, all designs, specifications and components are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)