

Female headers

BL 1 13 G

Stamped contact spring (fork contact), for \square 0.635 mm
V-notches permit breaking! Therefore any required number of contacts is available.

[add to](#)



Features	Technical Drawing	Accessories / related products
no. of contacts		12
contact material		CuSn-Legierung
surface contact / contact sleeve		Ni+0,2 μ m Au Ni+4...6 μ m Sn
surface of contact		gold-plated
Typ Innenfeder		Gabelkontakt
plugability		\square 0,5 mm bis \square 0,7 mm
insertion depth		1,5 ... 5,0 mm
plug-in cross-section		square 0.635
insertion / extraction force		1,5 N / 1,3 N
volume resistivity		\leq 10 m Ω
capacity between two adjacent contacts		\leq 0,9 pF
nominal current		3 A
nominal voltage		125 V AC
test voltage		1500 V
material isolation body		PPS
temperature range		-40 °C ... +163 °C (260 °C / 10 s)
class of flammability		UL 94 V-0
insulation resistance		$>10^{12}$ Ω
version		stamped contact spring (fork contact)
connection type		soldering
reflow solderable		yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Fisher](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)