

Application

- Horizontal and building backbone cable.
- Support current and future **Category 6 and Category 5 enhanced** applications, such as: 10 Base-T, 100 Base-T, 1000 Base-T (Gigabit Ethernet), FDDI, ATM

Key features and Standards

- General standards: **ISO/IEC 11801 2nd edition (2002)**, **EN 50173 2nd edition (2001)**, **ANSI/TIA/EIA 568-b.2 (2002)**

Construction & Dimensions



- Construction: Unshielded 4 twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 23 (0,57 mm)
- Conductor insulation material: Polyolefine
- Diameter over insulation: 1,01 mm
- Cross web: FRNC compound
- Jacket material: Flame retardant PVC
- Outer diameter: 6,20 mm

Pair 1	White-Blue/Blue
Pair 2	White-Orange/Orange
Pair 3	White-Green/Green
Pair 4	White-Brown/Brown

Colour identification according to IEC 60304

Electrical characteristics (at 20 °C)

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	70 Ohm/km
NVP - Nominal Velocity of Propagation	0.70 c
SKEW – Propagation delay difference (100 MHz)	typical \leq 15 ns/100m
Mean Characteristic Impedance 4-100 MHz ¹⁾	100 \pm 5 Ohm

¹⁾: According to cable requirements of ISO/IEC 11801 category 6, Sept. 2002.

General and environmental characteristics

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	25 mm
Minimum bending radius - installation	50 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Caloric value	490 kJ/m
Weight (approx.)	43.9 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.4 A

Electrical characteristics (at 20 °C)

Attenuation

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Max.) ¹⁾	-	4.0	6.0	7.6	8.5	10.8	15.5	19.9	25.3	29.2	33	dB/ 100m
Typical	[1.7]	3.5	5.6	7.1	8.0	10.1	14.4	18.6	23.6	27.0	30.7	dB/ 100m

NEXT (Near end crosstalk)

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) ¹⁾	-	66	60	57	56	53	48	45	42	41	39	dB/ 100m
Typical	[76]	73	66	64	63	56	55	52	49	48	45	dB/ 100m

Power sum NEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) ¹⁾	-	63	57	54	53	50	45	42	39	38	36	dB/ 100m
Typical	[74]	71	64	62	61	54	53	50	47	46	43	dB/ 100m

Power sum ELFEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) ¹⁾	-	53	45	41	39	35	29	25	21	19	17	dB/ 100m
Typical	[70]	64	57	51	49	45	39	35	31	29	27	dB/ 100m

ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) ¹⁾	-	62.0	54.0	49.4	47.5	42.2	32.5	25.1	16.7	11.8	6.0	dB/ 100m
Typical	[74]	70	60	57	55	46	41	33	25	21	14	dB/ 100m

Power sum ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) ¹⁾	-	59.0	51.0	46.4	44.5	39.2	29.5	22.1	13.7	8.8	3.0	dB/ 100m
Typical	[72]	68	58	55	53	44	39	31	23	19	12	dB/ 100m

Return Loss

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) ¹⁾	-	23.0	25.0	25.0	25.0	23.6	21.5	20.1	18.8	18.0	17.3	dB/ 100m
Typical	[33]	36	44	42	40	38	36	31	27	25	24	dB/ 100m

¹⁾: Specification values according to cable requirements of ISO/IEC 11801 category 6, Sept. 2002.

Note: Values between brackets are for information only

Ordering information

MARKING

Text on the cable jacket Inkjet printing

BELDEN 7965E UTP CAT6 4PR AWG23 ISO/IEC 11801 EN50173 VERIFIED 100 OHM

Meter marking: Yes

JACKET COLOUR

Colour	RAL code
Blue	RAL 5015

PACKAGING (PUT UP)

500m and 1000m Crate reels

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[0152660053](#) [603020002](#) [73-7797-25](#) [73-8890-10](#) [73-8890-14](#) [73-8891-14](#) [73-8891-25](#) [73-8892-50](#) [73-8894-10](#) [73-8894-3](#) [73-8895-14](#) [73-8896-7](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [9QA0-111-12-3.00](#) [1200650742](#) [1200700174](#) [1200860368](#) [1200650013](#) [1201080008](#) [1-21919-1](#) [1300500373](#) [1300101844](#) [1300101845](#) [130050-0004](#) [1300500014](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [MT14-187L](#) [17-103530](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC30BLY](#) [NK5EPC30VLY](#) [NK5EPC30YLY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [NK6PC30BUY](#) [NK6PC30GRY](#) [NK6PC30RDY](#) [NK6PC30Y](#) [NK6PC30YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#)