

FASCETTE IN NYLON 6.6 - NYLON 6.6 CABLE TIES



Articolo/Colore Type/Color		Dimensioni mm Dimension mm		Ø Max mm di serraggio	Resistenza min. alla trazione N	
Naturale Natural	Nero Black	Lunghezza Length	Larghezza Width	Max bundle Dia. mm	Min. tensile strength N	Conf. pezzi Packing pcs.
BM B0824*	BM N0824*	80	2,4	15	78	100/8000
BM B1025*	BM N1025*	100	2,5	22	80	100/5000
BM B1225*	BM N1225*	120	2,5	30	80	100/5000
BM B1625*	BM N1625*	160	2,5	40	80	100/4000
BM B2025*	BM N2025*	200	2,5	53	80	100/3000
BM B1436*	BM N1436*	140	3,6	33	180	100/2500
BM B2036*	BM N2036*	200	3,6	53	180	100/2000
BM B2936*	BM N2936*	300	3,6	76	180	100/1500
BM B3736*	BM N3736*	370	3,6	102	180	100
BM B1248*	BM N1248*	120	4,8	24	220	100/2000
BM B1648*	BM N1648*	160	4,8	38	220	100/1500
BM B1948*	BM N1948*	188	4,8	43	220	100/1500
BM B2048*	BM N2048*	200	4,8	50	220	100/1500
BM B2548*	BM N2548*	250	4,8	60	220	100/1300
BM B3048*	BM N3048*	300	4,8	76	220	100/1000
BM B3748*	BM N3748*	370	4,8	102	220	100
BM B3948*	BM N3948*	390	4,8	105	220	100
BM B4348*	BM N4348*	430	4,8	110	220	100
BM B5348*	BM N5348*	530	4,8	140	220	100
BM B1576*	BM N1576*	150	7,6	33	540	100/1000
BM B2076*	BM N2076*	200	7,6	50	540	100/800
BM B2976*	BM N2976*	300	7,6	76	540	100/600
BM B3776*	BM N3776*	368	7,6	102	540	100
BM B4576*	BM N4576*	450	7,6	132	540	100
BM B5476*	BM N5476*	533	7,6	140	540	100
BM B7576*	BM N7576*	750	7,6	218	540	100
BM B4390*	BM N4390*	430	9	110	790	100
BM B5390*	BM N5390*	526	9	140	790	100
BM B7190*	BM N7190*	710	9	190	790	100
BM B7890*	BM N7890*	776	9	228	790	100
BM B8190*	BM N8190*	815	9	239	790	100
BM B1090*	BM N1090*	1020	9	295	790	100
BM B1290*	BM N1290*	1220	9	365	790	100
BM B1590*	BM N1590*	1530	9	460	790	100

Materiale: Nylon 6.6

Classe di autoestinguenza: UL 94 - V 2
Temperatura d'esercizio: -40°C +85°C
Ottima resistenza agli olii, solventi, grassi e prodotti petroliferi in genere

* Le fascette possono essere fornite anche in buste da 1000 pezzi.
Per questa configurazione aggiungere la lettera M al codice prodotto.
Es. B0824 100 pz - B0824M 1000 pz.



Questo logo indica che i prodotti sono realizzati con materie plastiche esenti da alogeni, evitando, in caso di combustione, la formazione di gas tossici, in accordo con la norma internazionale EN 14582.

This logo indicates that the products are made with halogens free plastics, avoiding, in case of combustion, the formation of toxic gases, according to the International Standard EN 14582.

Material: Nylon 6.6

Self extinguish UL 94 - V 2
Operating Temperature: -40° to +85°C
Resistance to the oils, greasy, solvent and petroliferous products

* On request cable-ties are available with 1000 pcs bags.
Please add the letter M to article number.
Ex. B0824 100 pcs - B0824M 1000 pcs.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Ties](#) category:

Click to view products by [BM Group](#) manufacturer:

Other Similar products are found below :

[20093-0](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3526N BLACK 58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [20113-0](#)
[T56137](#) [3-350087-0](#) [CTB75X75BKA-C](#) [3722](#) [561-B110120](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-N3510](#) [561-TA250125](#) [08350-0](#) [08443-0](#)
[08600-0](#) [10035-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [10606-0](#) [561-EZ250](#) [561-EZ500](#) [561-EZ625](#) [561-EZ750](#) [561-TA00600](#) [SJ3519FR](#)
[BLACK 1X50](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [157-00039](#) [3719](#) [SJ-3401 BLACK 1"](#) [08445-0](#)
[08582-0](#) [08386-0](#) [10431-0](#) [08359-0](#) [10056-0](#) [10620-0](#) [10345-0](#) [10344-0](#) [08416-0](#) [08384-0](#) [08401-0](#)