



#### General ordering data

Order No.	1775600000
Part designation	ZDU 1.5/4AN BL
Version	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, blue, TS 35
EAN	4032248181636
Qty.	100 pc(s).

#### Product notes

Product description	Z-series standard ranges provide solutions for conductor cross-sections from 0.05 to 35 mm <sup>2</sup> .
---------------------	---

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA01ATEX2106U
Download, German	KEMA01ATEX2106U_d.pdf
Download English	KEMA01ATEX2106U_e.pdf
IECEEx Certificate of Conformity	IECEXULD05.0009U
Download	IECEXULD05.0009U_e.pdf
ATEX voltage	550 V
ATEX current	15 A
ATEX conductor cross-section	1.5 mm <sup>2</sup>
IECEEx voltage	550 V
IECEEx current	15 A
IECEEx conductor cross-section	1.5 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEEx-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

Colour of insulating material	blue
Connection direction	top
End plate required	Yes

#### Additional technical data

Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	4
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Clamped
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Feed-through terminal

#### CSA rating data

Voltage (CSA)	300 V
CSA current	20 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 14

#### Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Clamping range, min.	0.05 mm <sup>2</sup>
Clamping range, max.	1.5 mm <sup>2</sup>
Type of connection	Tension clamp connection
2nd type of connection	clamped
Connection direction	top
No. of connections	4
Stripping length	10 mm
Blade size	0.4 x 2.0 mm
Gauge to IEC 60947-1	B1
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	0.75 mm <sup>2</sup>
AWG conductor size, min.	AWG 30
AWG conductor size, max.	AWG 16
AWG conductor size, min.	0.13 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

AWG conductor size, max. 1.31 mm<sup>2</sup>

#### Dimensions

Width 3.5 mm  
 Height of lowest version 37 mm  
 Length 75.5 mm  
 TS 35 offset 42 mm

#### Rating data

Rated cross-section 1.5 mm<sup>2</sup>  
 Rated voltage 500 V  
 Rated impulse voltage 6 kV  
 Rated current 17.5 A  
 Standards IEC 60947-7-1  
 Current with max. conductor 17.5 A  
 Pollution severity 3

#### UL rating data

Voltage (UL) 300 V  
 Current (UL) 15 A  
 Min. cross-section (UL) AWG 30  
 Max. cross-section (UL) AWG 14

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0 EC000897  
 ETIM 3.0 EC000897  
 eClass 4.1 27-14-11-20  
 eClass 5.0 27-14-11-20  
 eClass 5.1 27-14-11-20

#### Similar products

Order No.	Part designation	Version
1775480000	ZDU 1.5	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, beige, TS 35

1826970000	ZDU 1.5/2X2AN	Feed-through terminal, 1.5 mm <sup>2</sup> , Clamping yoke connection, Wemid, dark beige, TS 35
1826990000	ZDU 1.5/2X2AN BL	Feed-through terminal, 1.5 mm <sup>2</sup> , Clamping yoke connection, Wemid, blue, TS 35
1827000000	ZDU 1.5/2X2AN OR	Feed-through terminal, 1.5 mm <sup>2</sup> , Clamping yoke connection, Wemid, Orange, TS 35
1775490000	ZDU 1.5 BL	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, blue, TS 35
1775500000	ZDU 1.5 OR	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, Orange, TS 35
1775530000	ZDU 1.5/3AN	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, beige, TS 35
1775540000	ZDU 1.5/3AN BL	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, blue, TS 35
1775550000	ZDU 1.5/3AN OR	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, Orange, TS 35
1775580000	ZDU 1.5/4AN	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, beige, TS 35
1775610000	ZDU 1.5/4AN OR	Feed-through terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, Orange, TS 35

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DIN Rail Terminal Blocks](#) category:*

*Click to view products by [Weidmuller](#) manufacturer:*

Other Similar products are found below :

[00110201060](#) [00110410002](#) [00110420002](#) [00110420004](#) [00110420202](#) [00110420302](#) [00110430002](#) [00110430402](#) [00110440002](#)  
[00175111500](#) [0117960000 AP SAK4-10](#) [0117980000 AP SAK4-10 BL](#) [0203069](#) [0205067](#) [0210421](#) [0260015](#) [0261014](#) [0261027](#) [0270018](#)  
[0271017](#) [0279560000 AP SAK2.5](#) [0279580000 AP SAK2.5 BL](#) [0302216](#) [0303370](#) [0303396](#) [0304298](#) [0305080](#) [0305226](#) [0305297](#) [0305352](#)  
[0308210](#) [0309086](#) [0309109](#) [0309112](#) [0309549](#) [0310321](#) [0310389](#) [0311087](#) [0311126](#) [0311142](#) [0311171](#) [031-12](#) [0311359](#) [0311540](#) [0311728](#)  
[0311760](#) [031-238](#) [0313085](#) [0321019](#) [0328920000 SAKS 3/35 G/5X30 500V](#)