


U.I. Lapp GmbH	PRODUCT INFORMATION	
	UNITRONIC® FD	07.11.2014

Highly flexible data transmission cable with PVC outer sheath for power chain use
Well-proven and reliable
Optimized cable construction for power chain use
Cost-effective solution



Power chain

Application range

Automated production processes require data transmission cables that offer high flexibility and durability
Suitable for use in measuring, control and regulating circuits
Assembly lines, production lines, in all kinds of machines

Product Make-up

Extra-fine wire strand made of bare copper wires
Core insulation made of PVC
Non-woven wrapping
Outer sheath made of PVC
Outer sheath colour: grey (RAL 7001)

Norm references / Approvals

Based on VDE 0812
For travel distances up to 10 m.
For use in power chains: Please comply with the assembly guidelines listed in Appendix T3


Product features

Low-adhesive surface
Flame-retardant according IEC 60332-1-2
Designed for 2 up to 8 million bending/unbending cycles in power chain applications

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils). Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: LAPP_PRO237EN.pdf	1 / 3
--------------------	-----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	
	UNITRONIC® FD	07.11.2014

Technical Data

Core identification code:	DIN 47100, refer to Appendix T9
Mutual capacitance:	C/C: approx. 100 nF/km
Peak operating voltage:	(not for power applications) 350 V
Classification:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Inductivity:	approx. 0.65 mH/km
Conductor stranding:	Stranded, extra-fine wire
Minimum bending radius:	Flexing: 5 x outer diameter Fixed installation: 3 x outer diameter
Test voltage:	1500 V
Temperature range:	Flexing: -5°C to +70°C Fixed installation: -40°C to +80°C

Product Management	Document: LAPP_PRO237EN.pdf	2 / 3
--------------------	-----------------------------	-------

Part number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)
UNITRONIC® FD			
0027841	3 x 0,14	3.9	4.2
0027842	4 x 0,14	4.2	5.6
0027843	5 x 0,14	4.5	7.0
0027844	7 x 0,14	5.1	9.8
0027845	10 x 0,14	6.1	14.0
0027846	14 x 0,14	6.2	19.6
0027847	18 x 0,14	6.8	25.2
0027848	25 x 0,14	8.3	35.0
0027855	2 x 0,25	4.3	5.0
0027856	3 x 0,25	4.5	7.5
0027857	4 x 0,25	4.9	10.0
0027858	5 x 0,25	5.3	12.5
0027859	7 x 0,25	6.1	17.5
0027860	10 x 0,25	7.4	25.0
0027861	14 x 0,25	7.5	35.0
0027863	18 x 0,25	8.5	45.0
0027865	25 x 0,25	10.4	62.5
0027870	2 x 0,34	4.7	6.8
0027871	3 x 0,34	5.0	10.2
0027872	4 x 0,34	5.4	13.6
0027873	5 x 0,34	5.9	17.0
0027874	7 x 0,34	6.8	23.8
0027875	10 x 0,34	8.5	34.0
0027876	14 x 0,34	8.6	47.6
0027877	18 x 0,34	9.7	61.2
0027878	25 x 0,34	11.9	85.0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Paired Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[7-21000-9](#) [9805 060100](#) [1213 009U1000](#) [1416402/M12MS/IP20/10](#) [9804 060100](#) [9808 060100](#) [9843 060100](#) [9873 060100](#) [190-038045-00](#)
[44A0121-12-996CS2275](#) [44A0121-20-09-MX](#) [55PC0211-14-9](#) [55PC0216-24-9](#) [55PC0221-22-2/6CS2756](#) [55PC0811-16-9](#) [55PC0811-24-9](#)
[55PC1131-20-029-9](#) [Y60912](#) [CW1922-000](#) [RI55D](#) [9157 060100](#) [2020D0309-0](#) [9774 060100](#) [8334 060100](#) [1350SB 0101000](#) [2412 0061000](#)
[8342 060100](#) [8740 060U1000](#) [9505 060U1000](#) [3613 003A1000](#) [44A0121-22-0/9-MX](#) [2412 009U1000](#) [82777 8771000](#) [9406 T35100](#) [2413](#)
[002A1000](#) [3613 D151000](#) [1533R 0101000](#) [1533P 0101000](#) [9272 006U1000](#) [2413F D15A500](#) [9681 0601000](#) [1533R 0061000](#) [RIT1000](#)
[1533R 006A1000](#) [9812 060100](#) [2221 B59U1000](#) [10GX13 D151000](#) [1874A 004A1000](#) [8340 060100](#) [8333 0601000](#)