



PRODUCT DATASHEET

Video Borescope/Wireless Inspection Camera

9mm camera diameter and 3.5" Color TFT LCD Wireless Monitor

with a 2GB microSD memory card (included) for capturing images (JPEG) or video (AVI) for viewing on your PC

Features:

- Detachable wireless color display can be viewed from a remote location up to 32ft (10m) from measurement point
- Captured video and still images with date/time stamp can be played back on the wireless monitor or your PC
- 9mm diameter camera head with 36" (0.9m) flexible gooseneck cable
- Video and images can also be transferred to your PC via the microSD card (with included SD adaptor) or USB cable (included) and viewed using Windows® Multimedia Player
- Menus in 10 languages: English, Chinese, German, French, Spanish, Portuguese, Italian, Japanese, Dutch, and Russian
- Mini water-proof (IP67) 9mm camera head for high resolution viewing
- · Four bright LED lamps with dimmer to illuminate viewed object
- Glare-free close-up field of view
- Optional BR200-EXT extension cable available for increasing viewing depth; 19mm diameter connector and 38" (0.96m) cable length; maximum 2 extension cables can be connected to the borescope

Applications:

- · Home inspection: Inspect in walls for mold, insect infestation, electrical wire or water pipe location
- HVAC: Inspect inside ducts, behind motors and compressors
- · Automotive: View inside or around engines and transmissions
- · Government: Safety and security inspections
- Industrial: Inspect weld integrity, process equipment, gears, molding machines
- Aerospace: Aircraft inspections for contamination, debris, cracks or other damage



display can be viewed from a remote location up to 32ft (10m) from the



Memory card included for capturing JPEG images and video (AVI) with date/time



4 built-in bright LED lights illuminates dark areas.



Ideal Applications: - Water Restoration - HVAC and Refrigeration

- Electrical inspection
- Automotive

Ordering Information:

BK25U	Flexible video Borescope (9mm diameter/1m cable, 110v adaptor)	
BR250-2	Flexible Video Borescope (9mm diameter/1m cable, 220V adaptor)	
BR250-4	Flexible Video Borescope (9mm diameter/1m cable, 240V adaptor)	
BR200-EXT	Borescope Extension Cable for BR250 (19mm diameter/0.9m cable)	
(Note: Personmended up to two PROOF EVT connected to PROFF to maintain recelution)		

(Note: Recommended up to two BR200-EXT connected to BR250 to maintain resolution)



Complete with 4 AA batteries. rechargeable display battery, microSD memory card with SD adaptor. USB cable, video interconnect cable, AC adaptor (100-240V. 50/60Hz), magnetic base stand, and hard case

Specifications		
Camera		
Pixels	640 x 480 (PAL)	
Transmission Frequency	2.4GHz	
Transmission Range	32ft (10m) unobstructed view	
Viewing direction	Viewing Angle 45°	
Focus distance from object	5.9" to 9.8" (15 to 25cm)	
Shaft diameter	9mm	
Working length	36" (0.9m)	
Minimum bend radius	2.36" (60mm)	
Camera Dimensions	7.3 x 5.7 x 1.6" (186 x 145 x 41mm)	
Weight	18.7oz (530g)	
Monitor		
LCD Screen Type	3.5" TFT	
Pixels	320 x 240	
Video Output Level	0.9 to 1.3V@75Ω	
Frame Rate	10, 15, 20, 25, 30FPS	
Video Resolution	960 x 240 (avi format)	
Image Resolution	640x 480 (jpeg format)	
Monitor Dimensions	3.9 x 2.7 x 1" (100 x 70 x 25mm)	
Operating/Charge Time	1.5 hours/3 hours	
Weight	4.9oz (140g)	



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160