



# NB 3.4 - 12 (12 V, 3.4 Ah)

Lead-acid NERBO batteries of NB series in AGM technology are designed for cyclical and buffer work. Nerbo batteries have an optimal price-quality ratio what makes them the best alternative for more expensive solutions. Their durability is designed for 5 years work at 20-25°C

# CHARACTERISTICS

Performance technology	VRLA-AGM
Nominal voltage	12 V
Nominal capacity (20 h/10.5 V, 25°C)	3.40 Ah
Maximum charge current	1,02 A
Maximum discharge current (5 sec)	51 A
Weight	~ 1.20 kg
Internal resistance (25°C)	~ 50 mΩ

Self-discharge drop by 3% of capacity after a month at 25  $^{\circ}\text{C}$ 

Case material

ABS (UL94HB, optional UL94V-0)

Alarm systems

Portable devices

Cash registers

ATION


Toys


Communication devices


Battery back-up


# MENSIONS

length	134 mm
width	67 mm
height	61 mm
total height	67 mm













### **CHARGE CHARACTERISTICS**

### Charged (ČA) 1. D ischarge 100% 2. Charge voltage 2.40V/cell 3. Charge current 0.20C(A) 4. Temperature 25°C 120 0.25 Charged Volum 15.0 100 Charge Voltage 0.20 80 0.15 14.0 60 0.10 13.0 0.05 20 12.0 0 12 14 16 18 Charging tim e (hours)


### **CAPACITY VERSUS VOLTAGE OCV**



### **DISCHARGE CHARACTERISTICS (25°C)**



### **SELF-DISCHARGE IN TIME**



### CONSTANT CURRENT CHARACTERISTICS (A at 25°C)

Cut-off voltage	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	12.1	7.89	6.22	3.48	2.11	1.17	0.84	0.67	0.57	0.31	0.17
9.90V	12.0	7.62	6.08	3.40	2.06	1.17	0.84	0.67	0.57	0.31	0.17
10.2V	11.3	7.33	5.82	3.30	2.00	1.16	0.83	0.66	0.56	0.31	0.17
10.5V	11.0	7.00	5.61	3.21	1.96	1.14	0.83	0.66	0.56	0.31	0.17
10.8V	10.1	6.58	5.32	3.08	1.91	1.11	0.80	0.64	0.54	0.30	0.16

### CONSTANT POWER CHARACTERISTICS (W at 25°C)

Cut-off voltage	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	138	88.3	71.1	39.4	24.5	13.7	10.0	8.02	6.83	3.74	2.01
9.90V	131	86.1	69.2	38.7	24.0	13.6	9.94	7.97	6.79	3.72	2.00
10.2V	127	82.5	66.8	38.0	23.1	13.5	9.87	7.92	6.75	3.70	1.99
10.5V	121	78.4	64.1	36.9	22.9	13.3	9.80	7.86	6.70	3.68	1.98
10.8V	111	74.5	61.0	35.1	22.1	13.0	9.51	7.62	6.50	3.61	1.94

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sealed Lead Acid Battery category:

Click to view products by Nerbo manufacturer:

Other Similar products are found below:

0809-0012 0819-0012 0850-0004 0859-0012 0800-0004 LC-R0612P LC-R061R3P PS-1250F1 APCRBC123 APCRBC124 LCRA1212P NP12-12 NP12-6 NP3.2-12 LC-P0612P LC-R063R4P LC-R067R2P1 LC-R122R2P LC-R0612P1 LC-R127R2P1 LC-X1220AP UP-VW1245P1 2320296 RBC32 RBC11A RBC36-SLT