

1. CONDUCTOR: 1/0. 50 ± 0. 005BC

ID: 0.94±0.02mm

MATERIAL:HDPE (210)
2. STANDING DIRECTION:RIGHT

3. FILLER: 500D NYLON PLASTIC

4. OD: 5. 2±0. 15mm

MATERIAL: 45P PVC COLOR: GREY

CORE COLOR:

blue/white&blue brown/white&brown orang/white&orang green/white&green

5. MAKING:

NETWORK SYSTEMS CABLE UTP ANSI TIA/EIA-568A 24AWG (4PR) OR ISO/IEC11801 VERIFIED CAT 5e (001-305M)

6. PACKING: 305M/R

REMAKE:

1. THE ID AND OD OF THE WIRE MUST BE EXACT, CAN NOT REDUCE THE CENTRE.

2. THICKNESS OF COAT BY EQUALITY: 0.5mm, THE LEAST THICKNESS: 0.45mm

3. THICKNESS OF CORE BY EQUALITY: 0.2mm, THE LEAST THICKNESS: 0.18mm

4. Impedance: $100 \Omega \pm 15\%$

Rating temperature: -20°C to 60°C

Standards: ISO/IEC11801, ANSI TIA/EIA-568A

VCOM International Ltd.			
	APPROVED BY CHECKED 1	SAM-AC-0032	DRING NO.
	APPROVED BY CHECKED BY DRAWN BY CUSTOMER PAGE		PRODUCT NO.
lof1	ÆR PAGE		TITLE:
mm	UNIT	CAT5E	
	SCALE	AT5E UTP 0.50BC	
)	,	
REV	A/0		
RESCRIPTION			
DATE	2010-9-30		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Cables / Networking Cables category:

Click to view products by Varta manufacturer:

Other Similar products are found below:

0152660053 603020002 73-7797-25 73-8890-10 73-8890-14 73-8891-14 73-8891-25 73-8892-50 73-8894-10 73-8894-3 73-8895-14 73-8896-7 MCJB2-10P6Q7-120 84909-0204 9QA0-111-12-3.00 1200650742 1200700174 1200860368 1200650013 1201080008 1-21919-1 1300500373 1300101844 1300101845 130050-0004 1300500014 1410147 E16A06002M030 E200102-009-S1 MT14-187L 17-103530 NK5EPC18RDY NK5EPC18VLY NK5EPC18YLY NK5EPC1GRY NK5EPC30BLY NK5EPC30VLY NK5EPC30YLY NK5EPC4Y NK5EPC6YLY NK5EPC8BLY NK5EPC9YLY NK6PC30BUY NK6PC30GRY NK6PC30RDY NK6PC30YLY 1969343-6 C501100010 C501106002