



## Cat.6 Surface Mounted Box UTP

### Technical Features

Categorie 6 Class E 250 MHz

ISO/IEC 11801 and ANSI/TIA/EIA 568B.2-1

1 or 2 RJ45 ports, unshielded

Easy surface installation

RAL 9010 pure white

Part no.	Port	EAN Code
NP0071	1-Port	4052792027921
NP0072	2-Port	4052792027938

### Package Contents

[www.logilink.com](http://www.logilink.com)



RoHS  
compliant



## Packaging Informations(NP0071)

Packing Dimension	80 x 80 x 50mm
Packing Weight	0.25kg
Carton Dimension	413 x 381 x 254mm
Carton Q'ty	250pcs
Carton Weight	42kg

## Packaging Informations(NP0072)

Packing Dimension	80 x 80 x 50mm
Packing Weight	0.25kg
Carton Dimension	413 x 381 x 330mm
Carton Q'ty	250pcs
Carton Weight	60.8kg



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Modular Connectors / Ethernet Connectors](#) category:*

*Click to view products by [Logilink](#) manufacturer:*

Other Similar products are found below :

[RJE231881317T](#) [MP1010RX-1000](#) [MP44RX-1000](#) [GAX-3-66](#) [GAX-8-62](#) [93606-0253](#) [GD-A-44](#) [GDCX-PA-66-50](#) [GDCX-PN-64](#) [GDCX-PN-66](#) [GDCX-PN-66-50](#) [GDLX-A-66](#) [GDLX-A-88](#) [GDLX-N-66](#) [GDLX-S-88K](#) [GDTX-S-88-50](#) [GDX-PA-1010](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-N-44M](#) [GLX-S-88M-BLK](#) [GMX-N-1010](#) [GMX-S-1010](#) [GMX-S-66](#) [GMX-SMT2-N-1010](#) [GMX-SMT2-N-64-50](#) [GMX-SMT2-S6-88](#) [GMX-SMT4-N-88](#) [GPX-2-64](#) [GRT1-BT1-5](#) [GSGX-N-2-88](#) [GSX-NS2-88-3.05](#) [GSX-NS2-88-3.05-50](#) [GSX-NS-88-3.05-30](#) [GSX-NS-88-3.05-50](#) [GSX-NS-88-3.68](#) [1-1775629-2](#) [GWLX-S-88-GR](#) [GWLX-S9-88-YG](#) [1300500326](#) [1300500227](#) [1300530003](#) [1300570002](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1400000](#) [1413176](#)