

Multicolour cables



Applications:
Flexible multicolour cables for wiring and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. insulation: PVC
Core colours: White, Pink, Light-blue, Yellow, Bright-orange, Grey, Green, Red, Violet, Blue, Brown, Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C106	5	5 x 0,35 (22 AWG)	11x0,20	1,8		4,7	100	M	3,0
C107	6	6 x 0,35 (22 AWG)	11x0,20	1,8		5,0	100	M	3,5
C108	7	7 x 0,35 (22 AWG)	11x0,20	1,8		5,4	100	M	4,0
C109	8	8 x 0,35 (22 AWG)	11x0,20	1,8		5,7	100	M	4,5
C110	10	10 x 0,35 (22 AWG)	11x0,20	1,8		6,3	100	M	5,5
C111	12	12 x 0,35 (22 AWG)	11x0,20	1,8		6,9	100	M	6,5



Applications:
Flexible sheathed cables for wiring and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. insulation: PVC
Core colours: Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey, Bright-orange, Green, Violet, Pink, White/red, White/black, White/blue, White/green, White/brown, White/yellow, White/violet, Blue/red, Blue/black, Blue/green, Blue/brown, Blue/yellow

External Sheath: PVC
Sheath colour: Black



Sheathed cables



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C158	6	6 x 0,25 (23 AWG)	8x0,20	1,4		5,3	100	B	4,5
C159	12	12 x 0,25 (23 AWG)	8x0,20	1,4		7,0	100	B	7,5
C160	16	16 x 0,25 (23 AWG)	8x0,20	1,4		8,0	100	B	10,0
C161	24	24 x 0,25 (23 AWG)	8x0,20	1,4		9,8	100	B	14,5

Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
75	49	-15 / +70
75	49	-15 / +70
75	49	-15 / +70
75	49	-15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[89182-010-1000](#) [89705-008-500](#) [6000FE-877-1000](#) [CS2885-000](#) [M27500-20SP2S23](#) [6300FE-877-U1000](#) [6309UE-877-1000](#) [M3905-BK005](#)
[6502FE 8771000](#) [6541PA-008-U1000](#) [CV6807-000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-](#)
[0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [752687-000](#) [768146-000](#) [773159-000](#)
[82841-877-5000](#) [83318E-009-500](#) [8348-060-500](#) [83559-002-1000](#) [83653-002-5000](#) [83659-002-1000](#) [83709-002-1000](#) [8404-060-500](#) [8469](#)
[060100](#) [858171-000](#) [8628-060-500](#) [868361-001](#) [8730-060-1000](#) [8737-060-U1000](#) [8747-060-100](#) [8747-060-1000](#) [8769-060-1000](#) [8775-060-](#)
[500](#) [877541-000](#) [8780-060-1000](#) [8782-001-U1000](#) [88444-002-1000](#) [9159-060-500](#) [939870-000](#) [9423 060U500](#) [9444 060U1000](#) [9497](#)
[0001000](#)