

Shielded flat audio cables



Applications:
Divisible ultra thin shielded flat cable for mini head-phones and for miniature electronic applications.

Characteristics:
 Conductors: O.F.C. tinned copper
 Cond. Insulation: PVC
 Core colours: Red, White
 Shields: Spiral covering 100%
 O.F.C. tinned copper
 PVC
 Sheath: Black
 Sheath colour: Black

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C117	2	2 x 0,08 (28 AWG)	12x0,10	0,9	1,8 x 3,8	200	B	2,5

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
210	70	300
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



Applications:
Divisible thin shielded flat cable for mini head-phones and for electronics. Suitable for the realization of audio assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: PVC
 Core colours: Red, White
 Shields: Spiral covering 100%
 O.F.C. red copper
 PVC
 Sheath: Black
 Sheath colour: Black

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C124	2	2 x 0,12 (26 AWG)	16x0,10	1,1	2,4 x 5,0	100	B	2,2

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
140	70	340
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



Applications:
Divisible shielded flat cable for head-phones and for sound reproduction. Suitable for the realization of audio assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: PVC
 Core colours: Red, Yellow
 Shields: Spiral covering 100%
 O.F.C. red copper
 PVC
 Sheath: Black, Red, Blue, Yellow, Green, White
 Sheath colours: Black, Red, Blue, Yellow, Green, White

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C118	2	2 x 0,14 (26 AWG)	18x0,10	1,4	2,9 x 5,8	100	B	2,8

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
130	65	280
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)