

Microphone cables



Applications:
Unbalanced microphone cable and for sound reproduction.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: Compact PE
 Core colour: Transparent
 Shield: Braided covering 90%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Black



| tasker® Code | Cond. number | Nominal section mm ² | Cond. Format. mm. | External Core Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|------------------------------------|----------------------|------------------------|--------------------------------|------------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C129 | 1 | 1 x 0,35 (22 AWG) | 11x0,20 | 3,0 | 5,2 | 100 | B | 3,5 |

nightly blue®



| Conductor Resistance Ω/Km ± 5% | Capacity Core/core pF/mt | Capacity Core/shield pF/mt |
|-----------------------------------|--------------------------------|---------------------------------------|
| 60 | | 89 |
| | Max rated Voltage AC - V 49 | Operative Temperature °C -15 / +70 |



Applications:
Unbalanced microphone cable and for sound reproduction.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: Compact PE
 Core colour: Transparent
 Shield: Braided covering 100%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Transparent

| tasker® Code | Cond. number | Nominal section mm ² | Cond. Format. mm. | External Core Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|------------------------------------|----------------------|------------------------|--------------------------------|------------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C195 | 1 | 1 x 0,50 (20 AWG) | 16x0,20 | 2,1 | 6,0 | 100 | B | 4,2 |

nightly blue®



| Conductor Resistance Ω/Km ± 5% | Capacity Core/core pF/mt | Capacity Core/shield pF/mt |
|-----------------------------------|--------------------------------|---------------------------------------|
| 45 | | 130 |
| | Max rated Voltage AC - V 49 | Operative Temperature °C -15 / +70 |



Applications:
Professional unbalanced microphone cable and for sound reproduction.

Characteristics:
 Conductor: O.F.C. red copper
 Cond. Insulation: PVC
 Core colour: White
 Inner cotton: Braided covering 95%
 Shield: Braided covering 95%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colours: Red, Blue, Yellow, Green

| tasker® Code | Cond. number | Nominal section mm ² | Cond. Format. mm. | External Core Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|------------------------------------|----------------------|------------------------|--------------------------------|------------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C209 | 1 | 1 x 0,75 (18 AWG) | 24x0,20 | 3,0 | 6,2 | 100 | B | 5,3 |

| Conductor Resistance Ω/Km ± 5% | Capacity Core/core pF/mt | Capacity Core/shield pF/mt |
|-----------------------------------|--------------------------------|---------------------------------------|
| 30 | | 236 |
| | Max rated Voltage AC - V 49 | Operative Temperature °C -15 / +70 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)