



PRODUCT NO	NO OF POS	DIM A	DIM B	DIM C	OVERPLATING	UNDERPLATING	STYLE	POSITIONS POLARIZED	LF OPTION
65461-001	2x8	.800/20.32	.700/17.78	.09/2.3	30u"/.76u GOLD	50u"/1.27u NICKEL	P	NDNE	↓
-002	2x9	.900/22.86	.800/20.32				P		↓
-003	2x10	1.000/25.40	.900/22.86				M		↓
-004	2x12	1.200/30.48	1.100/27.94				P		↓
-005	2x13	1.300/33.02	1.200/30.48				M		↓
-006	2x17	1.700/43.18	1.600/40.64				M		↓
-007	2x20	2.000/50.80	1.900/48.26				M		↓
-008	2x25	2.500/63.50	2.400/60.96				M		↓
-009	2x8	.800/20.32	.700/17.78		150u"/3.81u TIN		P		↓
-010	2x9	.900/22.86	.800/20.32				P		↓
-011	2x10	1.000/25.40	.900/22.86				M		↓
-012	2x12	1.200/30.48	1.100/27.94				M		↓
-013	2x13	1.300/33.02	1.200/30.48				M		↓
-014	2x17	1.700/43.18	1.600/40.64				M		↓
-015	2x20	2.000/50.80	1.900/48.26				M		↓
-016	2x25	2.500/63.50	2.400/60.96				M		↓
-017	2x14	1.400/35.56	1.300/33.02		150u"/3.81u TIN		M		↓
-018	2x14	1.400/35.56	1.300/33.02		30u"/.76u GOLD		M		↓
-019	2x5	.500/12.70	.400/10.16		30u"/.76u GOLD		M		↓
-020	2x5	.500/12.70	.400/10.16		150u"/3.81u TIN		M		↓
-021	2x8	.800/20.32	.700/17.78	.49/12.4	30u"/.76u GOLD		M		↓
-022	2x5	.500/12.70	.400/10.16	.15/3.8	50u"/1.27u GOLD		M		↓
-023	2x5	.500/12.70	.400/10.16	.15/3.8	50u"/1.27u GOLD		M		↓
-024	2x8	.800/20.32	.700/17.78	.15/3.8	50u"/1.27u GOLD		M		↓
-025	2x7	.700/17.78	.600/15.24	.09/2.3	30u"/.76u GOLD		M		↓
-026	2x7	.700/17.78	.600/15.24	.09/2.3	150u"/3.81u TIN		M		↓
-027	2x10	1.000/25.40	.900/22.86	.15/3.8	50u"/1.27u GOLD		M		↓
-028	2x8	.800/20.32	.700/17.78	.15/3.8	50u"/1.27u GOLD		M		↓
-029	2x10	1.000/25.40	.900/22.86	.09/2.3	30u"/.76u GOLD		M		↓
-030	2x14	1.400/35.56	1.300/33.02	.09/2.3	30u"/.76u GOLD		M		↓
-031	2x20	2.000/50.80	1.900/48.26	.09/2.3	50u"/1.27u GOLD		M		↓
-032	2x8	.800/20.32	.700/17.78	.15/3.8	50u"/1.27u GOLD		M		↓
-033	2x17	1.700/43.18	1.600/40.64	.15/3.8	30u"/.76u GOLD		M		↓
-034	2x3	.300/7.62	.200/5.08	.09/2.3			M		↓
-035	2x6	.600/15.24	.500/12.70	.09/2.3			M		↓
-036	2x24	2.400/60.96	2.300/58.42	.09/2.3			M		↓
-037	2x20	2.000/50.80	1.900/48.26	.49/12.4			M		↓
-038	2x5	.500/12.70	.400/10.16	.09/2.3			M		↓
-039	2x8	.800/20.32	.700/17.78	.15/3.8			M		↓
-040	2x13	1.300/33.02	1.200/30.48				M		↓
-041	2x10	1.000/25.40	.900/22.86				M		↓
-042	2x5	.500/12.70	.400/10.16				M		↓
65461-001	2x20	2.000/50.80	1.900/48.26	.15/3.8	30u"/.76u GOLD	50u"/1.27u NICKEL	M	NDNE	↑

mat'l. code		itr	ecn no	dr	date
tolerances unless otherwise specified		linear			
.XXX±.01/.X±.3		.XXX±.005/.XXX±.13			
.XXX±.0020/.XXX±.051		.XXX±.0020/.XXX±.051			
angles		0° ±.2°			
dr		R SEPLE 4-2-90			
engr		H SUNDY 4-2-90			
chr		H SUNDY 4-2-90			
dppd		H SUNDY 4-2-90			
sheet		revision			
index		sheet			

CUSTOMER COPY		FCI		www.fciconnect.com	
title		RIGHT ANGLE HEADER		TOP SHIELDED	
product family		HEADERS		code	
size		dwg no		213	
scale		1:1		sheet	
INCH/MM		65461		3 of	
cage code		22526		4	



PRODUCT NO	NO OF POS	DIM A	DIM B	DIM C	OVERPLATING	UNDERPLATING	STYLE	POSITIONS POLARIZED	LF OPTION
65461-044	2x12	1.200/30,48	1.100/27,94	2,6/6,6	30u"/.76u GOLD	50u"/1,27u NICKEL	M	NONE	↓
-045	2x36	3.600/91,44	3.500/88,90	.09/2,3	↓	↓	M	NONE	↓
-046	2x10	1.000/25,40	.900/22,86	.15/3,8	↑	↑	M	NONE	↓
-048	2x10	1.000/25,40	.900/22,86	.09/2,3	↑	↑	M	NONE	↓
-049	2x10	1.000/25,40	.900/22,86	.09/2,3	↑	↑	M	NONE	↓
-050	2x14	1.400/35,56	1.300/33,02	.18/4,6	↑	↑	M	NONE	↓
-051	2x17	1.700/43,18	1.600/40,64	.09/2,3	↑	↑	M	NONE	↓
-052	2x3	.300/7,62	.200/5,08	.09/2,3	↑	↑	M	NONE	↓
-053	2x5	.500/12,70	.400/10,16	.09/2,3	↑	↑	P	B-4	↓
-054	2x13	1.300/33,02	1.200/30,48	.09/2,3	↑	↑	M	NONE	↓
-055	2x10	1.000/25,40	.900/22,86	.15/3,8	↑	↑	M	RDW B	↓
-059	2x10	1.000/25,40	.900/22,86	.15/3,8	↑	↑	M	RDW B	↓
-060	2x14	1.400/35,56	1.300/33,02	.15/3,8	↑	↑	M	RDW B	↓
-061	2x20	2.000/50,80	1.900/48,26	.11/2,8	↑	↑	M	NONE	↓
-062	2x12	1.200/30,48	1.100/27,94	.11/2,8	↑	↑	M	NONE	↓
-063	2x17	1.700/43,18	1.600/40,64	.11/2,8	↑	↑	M	NONE	↓
-064	2x25	2.500/63,50	2.400/60,96	.11/2,8	↑	↑	M	NONE	↓
-065	2x13	1.300/33,02	1.200/30,48	.11/2,8	↑	↑	M	NONE	↓
-066	2x10	1.000/25,40	.900/22,86	.15/3,8	↑	↑	M	RDW-B	↓
-067	2x14	1.400/35,56	1.300/33,02	.15/3,8	↑	↑	M	RDW-B	↓
-068	2x20	2.000/50,80	1.900/48,26	.11/2,8	↑	↑	M	NONE	↓
-069	2x8	.800/20,32	.700/17,78	.09/2,3	↑	↑	M	NONE	↓
-070	2x13	1.300/33,02	1.200/30,48	.09/2,3	↑	↑	P	NONE	↓
-071	2x14	1.400/35,56	1.300/33,02	.11/2,8	↑	↑	M	NONE	↓
-072	2x32	3.200/81,28	3.100/78,74	.11/2,8	↑	↑	P	NONE	↓
-073	2x15	1.500/38,106	1.400/35,56	.11/2,8	↑	↑	M	NONE	↓
-074	2x30	3.000/76,20	2.900/73,66	.11/2,8	↑	↑	M	NONE	↓
65461-075	2x17	1.700/43,18	1.600/40,64	.11/2,8	30u"/.76u GXT	50u"/1,27u NICKEL	P	NONE	↑

mat'l. code		itr	ecn no	dr	date	linear	angles	dr	engr	chr	ppd	sheet	revision	index
tolerances unless otherwise specified		.XXX±.01/.X±.3				.XXX±.005/.XXX±.13	0 ±.2	R SEPLE	H SUNDY	H SUNDY	H SUNDY			
CUSTOMER COPY		projection	INCH/MM	scale	1:1	product family	size	dwg no	code	code	sheet	4 of	sheet	4 of
FCI		RIGHT ANGLE HEADER	TOP SHIELDED	HEADERS	65461	213	213	213	213	213	213	213	213	213
www.fciconnect.com														

PDM: Rev:AL		STATUS: Released		ACAD	
22526		22526		22526	
4		3		1	
4		3		1	
4		3		1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [FCT Electronics](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)