

Spiral shielded cables



Applications:
Flexible cables with separately shielded and insulated cores for sound reproduction and electronics.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: PVC
 Core colours: Blue, White, Red, Yellow, Green, Blue, Grey, Orange, Pink, Brown, Light-Blue, Violet
 Shields: Spiral covering 100%
 O.F.C. red copper
 Inner sheaths: PVC – red colour
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C122	4	4 x 0,14 (26 AWG)	18x0,10	1,1	2,2	8,0	100	B	9,5
C120	6	6 x 0,14 (26 AWG)	18x0,10	1,1	2,2	9,3	100	B	11,6
C201	8	8 x 0,14 (26 AWG)	18x0,10	1,1	2,2	10,0	100	B	16,3
C163	12	12 x 0,14 (26 AWG)	18x0,10	1,1	2,2	14,0	100	B	20,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
130	80	340
130	80	340
130	80	340
130	80	340
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70



Applications:
Flexible cable for sound reproduction and electronics.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: PVC
 Core colours: Red, Blue, Yellow, Brown, White, Grey, Black
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C182	7	7 x 0,25 (23 AWG)	8x0,20	1,5	6,3	100	B	6,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
75	120	210
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)