

Unipolar flexible cables



RoHS
Conformity

Applications:
Unipolar flexible cable for electronics.

Characteristics:
 Conductor: O.F.C. red copper
 C130 PVC
 Insulation: C131 PVC HT 105°
 Sheath colours: **White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet**

tasker® Code	Cond. number	Nominal section mm²	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C130	1	1 x 0,22	24	7x0,20	1,2	200	B	0,7
C131		1 x 0,35	22	11x0,20	1,4 PVC HT 105°	200	B	1,0

Production on demand

RoHS
Conformity

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
90	49	-15 / +70
60	49	-15 / +90

Unipolar cable with Stiff Wire 6/10



Applications:
Unipolar cable with stiff wire 6/10 in tinned copper for electronics.

Characteristics:
 Conductor: O.F.C. tinned copper
 Insulation: PVC
 Sheath colours: **Black, White, Red, Green, Blue, Yellow**

tasker® Code	Cond. number	Nominal section mm²	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C133	1	1 x 0,28	23	1x0,60 (6/10)	1,2	200	B	0,9

RoHS
Conformity

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
70	49	-15 / +70

Unipolar flexible cable



Applications:
Unipolar flexible cable for tester and measuring devices.
Conductor composed of n° 64 of Ø mm. 0,10 copper wires.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: PVC
 Sheath colours: **Black, Red**

tasker® Code	Cond. number	Nominal section mm²	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C205	1	1 x 0,50	20	64x0,10	2,5	100	B	1,3

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
45	49	-15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Leads](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[R928010000](#) [R928142000](#) [1301430020](#) [15101](#) [15115](#) [15117](#) [15301](#) [15303](#) [15304](#) [15102](#) [15120](#) [15308](#) [15408](#) [15302](#) [15306](#) [15307](#) [15502](#)
[15403](#) [15407](#) [15409](#) [15501](#) [15506](#) [EM3782-12-7#](#) [EM4702-12-0](#) [BU-1149-A-36-0](#) [BU-1481-E-12-0](#) [BU-1481-E-24-0](#) [2524-A-60](#) [924961-C](#)
[924964-C](#) [924966-C](#) [924967-C](#) [LB1F-2R-RED](#) [LB1F-2R-YLW](#) [2500](#) [2501](#) [2524-A-48](#) [2977-J-48](#) [R928051000](#) [R928141000](#) [R928143000](#)
[R948131000](#) [BU-1449-E-12-2](#) [BU-1480-E-24-0](#) [BU-1481-E-12-2](#) [BU-1481-E-24-2](#) [LB1F-2R-BLK](#) [LB1F-2R-BLUE](#) [EM3542-1#](#) [EM3782-12-8#](#)