



**Applications:**  
Special flat cable composed of: 1 mini-coaxial cable and 2 shielded cores for special video applications and suitable for the realization of average distance video and audio stereo assembly.

**Characteristics:**

**Coaxial cable**

Conductor: stranded in O.F.C. red copper  
PEE  
Insulation: PVC  
Shield: Spiral covering 100%  
O.F.C. tinned copper

**Shielded cores**

Conductors: stranded in O.F.C. red copper  
Insulations: PVC  
Core colours: Red, Yellow  
Shields: Spiral covering 100%  
O.F.C. red copper  
PVC  
Total Sheath: PVC  
Sheath colour: Black



tasker® Code	Cond. number	Cond. Number Nominal section	Cond. Format.	External Core	External Inner Sheath	External Cable Dimension	Reel or Spool (* pag. II)		
							mm.	mm.	mm.
C228	1	1 x 75 Ω (0,08 mm <sup>2</sup> )	10x0,10	1,5		3,4x10,4	100	B	6,5
	+2	+2 x 0,14 (26 AWG)	18x0,10	1,5					

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
130		50		250	
Velocity of propagation of coax %	Impedance Ω ± 3%	Max rated Voltage V	Operative Temperature °C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,5	28,5	41,7	60,2	87,3	103,0



**Applications:**  
Special round cable composed of: 1 mini-coaxial cable and 2 shielded cores for special video applications and suitable for the realization of average distance video and audio stereo assembly.

**Characteristics:**

**Coaxial cable**

Conductor: stranded in O.F.C. tinned copper  
Insulation: PPE  
Shield: Braided covering 90%  
O.F.C. tinned copper

**Sheath:**

Sheath colours: Black

**Insulated shielded cores**

Conductors: stranded in O.F.C. red copper  
Insulations: PE  
Core colours: Red, Yellow  
Shields: Spiral covering 100%  
O.F.C. red copper

**Sheaths:**

Sheath colours: Black

Waste filler among elements

Total taping: unweaved Polyester

Total Sheath: Flame Retardant

PVC CEI 20-22/II\*

Sheath colour: Black



tasker® Code	Cond. number	Cond. Number Nominal section	Cond. Format.	External Core	External Inner Sheath	External Cable Diameter	Reel or Spool (* pag. II)		
							mm.	mm.	mm.
C229	1	1 x 75 Ω (0,08 mm <sup>2</sup> )	10x0,10	1,5	2,7	7,5	100	B	7,5
	+2	+2 x 0,22 (24 AWG)	28x0,10	1,5	2,6				

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
90		45		140	
Velocity of propagation of coax %	Impedance Ω ± 3%	Max rated Voltage V	Operative Temperature °C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,5	28,5	41,7	60,2	87,3	103,0

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:*

*Click to view products by [Tasker](#) manufacturer:*

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)