

Transparent flat cables

RoHS
Conformity

Applications:

Transparent flat cable.
Cable for electronics, loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:

Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper
Insulation: Special PVC
Sheath colour: Transparent



tasker® Code	Cond. number	Nominal section mm²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)			
						mt.	Type	Kg.	
C103 TN	2	2 x 0,22	24	0,20	1,8 x 3,7	100	B	1,0	
C105 TN		2 x 0,75	18	0,20	2,4 x 4,8	100	B	2,5	
C203 TN		2 x 1,00	17	0,20	2,8 x 5,6	100	B	3,0	
C237 TN		2 x 1,50	14	0,20	3,0 x 6,0	100	B	4,1	
C238 TN		2 x 2,00	12	0,25	3,5 x 7,0	100	B	5,5	
C100 TN		2 x 3,00	11	0,25	3,8 x 7,7	100	B	8,0	
C134 TN		2 x 4,00	10	0,25	4,1 x 8,2	50	B	4,5	
C135 TN		2 x 6,00	10	0,25	4,1 x 8,2	50	B	8,0	
					17x7x0,20	6,1 x 14,0			
					25x7x0,20				

RoHS
Conformity

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
90	49	-15 / +70
32	49	-15 / +70
21	49	-15 / +70
16	49	-15 / +70
14	49	-15 / +70
9	49	-15 / +70
6	49	-15 / +70
5	49	-15 / +70

RoHS
Conformity

Applications:

Professional Transparent flat cable for loudspeakers, Home Theatre and Hi-Fi Car systems.

Cable with conductors composed of extremely thin elementary wires (from n° 126 to n° 315 of Ø mm. 0,10) that are first bound up in beams and then stranded for a better transmission of the audio signal.

Characteristics:

Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper
Insulation: Special PVC
Sheath colour: Transparent

Special Extra-flex transparent flat cables



tasker® Code	Cond. number	Nominal section mm²	Nominal section AWG	Cond. Format. mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C191 TS	2	2 x 1,00	17	18x7x0,10	2,8 x 5,6	100	B	3,2
C192 TS		2 x 1,50	16	27x7x0,10	3,0 x 6,0	100	B	4,2
C193 TS		2 x 2,50	13	45x7x0,10	3,8 x 7,7	100	B	6,5
C100 TS		2 x 3,00	12	25x7x0,15	5,8 x 11,2	100	B	12,0

RoHS
Conformity

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
21	49	-15 / +70
16	49	-15 / +70
12	49	-15 / +70
9	49	-15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)