

Microphone cables



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C202	2	2 x 0,08 (28 AWG)	12x0,10	0,9	3,0	100	B	1,6



Applications:
Extra flex balanced mini-microphone cable for miniature applications.

Characteristics:
 Conductors: O.F.C. tinned copper
 Cond. Insulation: PVC
 Core colours: Red, White
 Shield: Spiral covering 100%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Black



Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
210	170	310
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C286	2	2 x 0,22 (24 AWG)	28x0,10	1,1	3,8	100	B	2,5



Applications:
Extra flex balanced microphone cable for audio multiline and/or wiring applications.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Core colours: Red, Transparent
 Textile fillers between conductors
 Drain wire: O.F.C. tinned copper
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: Flame Retardant PVC
 CEI 20-22/II°
 Sheath colour: Black



Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	75	160
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C280	2	2 x 0,22 (24 AWG)	28x0,20	1,1	4,8	100	B	3,5



Applications:
Balanced microphone audio cable for wiring applications.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Core colours: Red, Transparent
 Textile fillers between conductors
 Total taping in unweaved polyester
 Drain wire: O.F.C. tinned copper
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Blue



Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	75	160
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)