Product Specifications

COMMSCOPE®

6-569530-2 | MP-88S-R-5

Modular Plug, 8P/8C, Shielded, Round, 500 pcs

Body Features

Conductor Type	Solid	Stranded
Shield Material	Copper alloy
Shield Plating Material	Nickel

Configuration Features

Number of Positions	8
Keyed	No

Contact Features

Contact Base Material	Phosphor bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 µin	1.27 µm
Number of Contacts Loaded	8

Dimensions

Cable Jacket Outside Diameter Range	0.20 in	5.1 mm
Conductor Outside Diameter	0.034–0.039 in	0.86–0.99 mm
Conductor Wire Size	26–24 AWG

Housing Features

Housing Material	Glass filled polycarbonate

Industry Standards

UL Flammability Rating	UL 1863

Packaging Features

Packaging Quantity	500

Product Availability

Region	Asia	Australia/New Zealand	EMEA	Latin America	North America

Product Type Features

Cable Type	Round, shielded
Performance Category	Category 5

6-569530-2 | MP-88S-R-5

Connector Style	Plug
Jack Type	RJ45
Latch Style	Standard
Product Type	Connector
Shielded	Yes

Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors *category:*

Click to view products by Commscope *manufacturer:*

Other Similar products are found below :

RJE231881317T MP1010RX-1000 MP44RX-1000 GAX-3-66 GAX-8-62 93606-0253 GD-A-44 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-A-88 GDLX-N-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-A-44 GLX-N-1010M-BLK GLX-N-44M GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT2-N-1010 GMX-SMT2-N-64-50 GMX-SMT2-S6-88 GMX-SMT4-N-88 GPX-2-64 GRT1-BT1-5 GSGX-N-2-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-30 GSX-NS-88-3.05-50 GSX-NS-88-3.68 1-1775629-2 GWLX-S-88-GR GWLX-S9-88-YG 1300500326 1300500227 1300530003 1300570002 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1400000 1413176