Product Specifications





6-569550-3 | MP-5ES-1 | Modular Plug, 8P/8C, Shielded, Round, 100 pcs

Body Features

Conductor Type Solid | Stranded Shield Material Copper alloy Shield Plating Material Nickel

Configuration Features

Number of Positions 8
Keyed No

Contact Features

Contact Base Material Phosphor bronze

Contact Mating Area Plating Material Gold

Contact Mating Area Plating Thickness 50.00 µin | 1.27 µm

Number of Contacts Loaded 8

Dimensions

Cable Jacket Outside Diameter Range 0.190-0.220 in $\mid 4.8-5.6$ mm Conductor Outside Diameter 0.034-0.039 in $\mid 0.86-0.99$ mm

Conductor Wire Size 26–23 AWG

Housing Features

Housing Material Glass filled polycarbonate

Industry Standards

UL Flammability Rating UL 1863

Packaging Features

Packaging Quantity 100

Product Availability

Region Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Features

Cable Type Round, shielded
Performance Category Category 5
Connector Style Plug

Product Specifications



6-569550-3 | MP-5ES-1

Jack TypeRJ45Latch StyleStandardProduct TypeConnectorShieldedYes

Termination Features

Termination Method to Wire/Cable Insulation Displacement Crimp (IDC)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Commscope manufacturer:

Other Similar products are found below:

RJE231881317T MP1010RX-1000 MP44RX-1000 GAX-3-66 GAX-8-62 93606-0253 GD-A-44 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-A-88 GDLX-N-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-A-44 GLX-N-1010M-BLK GLX-N-44M GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT2-N-1010 GMX-SMT2-N-64-50 GMX-SMT2-S6-88 GMX-SMT4-N-88 GPX-2-64 GRT1-BT1-5 GSGX-N-2-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-30 GSX-NS-88-3.05-50 GSX-NS-88-3.68 1-1775629-2 GWLX-S-88-GR GWLX-S9-88-YG 1300500326 1300500227 1300530003 1300570002 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1400000 1413176