Products

Industries

Resources

About TE

My Account

Innovation

Support Center

What can we help you find?

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details

2041376-1 Product Details

🗓 Share







2041376-1

PCB Mounted Jacks - Single Port, Multi-port and Stacked

Not reviewed for RoHS Compliance

Product Highlights:

- Connector
- Preloaded
- Stacked Port Configuration
- 2 x 2 Jack Configuration
- Jack Type = RJ45

View all Features

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product











Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Additional Information:

Product Line Information

Related Products:

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Side Entry (Right Angle)
- PCB Mount Style = Through Hole
- Performance Category = Cat 3
- LED = With
- Grounding Options = Panel Ground and PCB Ground
- Panel Stops = Without
- Keyed = No
- Profile = Standard
- Color = Black

- Number of PCB Ground Tabs = 4

Mechanical Attachment:

• Panel Mount Retention = Without

Termination Features:

• Termination Method to PC Board = Solder

Dimensions:

- Height (mm [in]) = 25.30 [0.996]
- PCB Tail Length (mm [in]) = 2.54 [0.100]

Body Features:

- Inverted Jack Face = No
- Shield Plating = Nickel
- Shield Material = Brass

Contact Features:

- Solder Tail Contact Plating = Gold Flash over Nickel
- Contact Plating, Mating Area, Material = Gold (6)
- Contact Base Material = Phosphor Bronze

Housing Features:

• Housing Material = High Temperature Thermoplastic

Configuration Features:

- Preloaded = Yes
- Port Configuration = Stacked
- Jack Configuration = 2 x 2
- Number of Positions = 8
- Shielded = Yes
- Number of Contacts Loaded = 8

Industry Standards:

- RoHS/ELV Compliance = Not reviewed for ELV/RoHS compliance
- Lead Free Solder Processes = Not reviewed for lead free solder
- UL Flammability Rating = UL 94V-0

Identification Marking:

- LED Position 3 Color = None • LED Color; Top Left = Green
- LED Color; Top Right = Yellow
- LED Color; Bottom Left = Green
- LED Color; Bottom Right = Yellow

Packaging Features:

Packaging Method = Tray

Product Availability:

• Region = Asia, North America

Other:

• Brand = TE Connectivity

Corporate Information

About TE Investors News Room Supplier Portal **Quick Links Distributor Inventory**

Product Cross Reference Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us Find a Phone Number Knowledge Base

Manage Your Account











Terms & Conditions

Careers

Privacy Policy AODA Accessibility Policy AODA Multi-Year Accessibility Plan

© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved

[+] Provide Website Feedback

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

RJE231881317T MP1010RX-1000 MP44RX-1000 GAX-3-66 GAX-8-62 93606-0253 GD-A-44 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-A-88 GDLX-N-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-A-44 GLX-N-1010M-BLK GLX-N-44M GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT2-N-1010 GMX-SMT2-N-64-50 GMX-SMT2-S6-88 GMX-SMT4-N-88 GPX-2-64 GRT1-BT1-5 GSGX-N-2-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-30 GSX-NS-88-3.05-50 GSX-NS-88-3.68 1-1775629-2 GWLX-S-88-GR GWLX-S9-88-YG 1300500326 1300500227 1300530003 1300570002 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1400000 1413176