

## LED light bar OPBxx5630-02924WL - PRODUCT DATASHEET



<b>Voltage</b>	24 V DC
<b>Power</b>	11,0 W/m
<b>Luminocity</b>	1320 lm/m
<b>Qty LED</b>	29 LED/m
<b>Distance between LED</b>	34,2 mm
<b>Can be cut into section</b>	24 cm

Powered by

### Basic information:

- PL LINE PRODUCT- PROFESSIONAL LINE, HIGHEST QUALITY, LUMINOSITY AND DURABILITY
- PROFESSIONAL PCB MOUNTING, ONLY BRAND-NAME LED DIODES (LITEON)
- MODULES CAN BE SPLIT INTO 24 CM SECTIONS (7LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTION WITH ONE POWER-SUPPLY POINT: 5M)

### Typical application:

- UTILITY, DECORATIVE LIGHTING
- CEILING, WALL, NICHE, SHELF, PASSAGEWAYS BACKLIGHTING
- ADVERTISING (SIGNBOARDS): SHOP, MUSEUM, TARDE FAIRS EXPOSITIONS ETC.
- KITCHEN WORKTOPS LIGHTING

### Explanation:

- "xx" - COLOR DESIGNATION E.G. WH, WN AND WW



UWAGA  
ZACHWAĆ OSTROŻNOŚĆ  
ELEMENTY SKŁADNIWE  
NIE WYKAZUJĄCĄ  
ELEKTROSTATYCZNE



PRODUKT WYKONANY  
Z PROCEZSPÓŁNY  
ZGODNYCH Z NORMĄ  
RoHS



IP20

### Additional Information

Color	Cool white WH	Cool white WH	Warm white WW	Warm white WW	Neutral white WN	Warm white WW
<b>Voltage</b>				24 V DC		
<b>Power</b>				8,0 W/m		
<b>Power of single LED</b>				0,27 W		
<b>Current</b>				0,33 A/m		
<b>Luminocity</b>	1320 lm/m	1320 lm/m	1280 lm/m	1280 lm/m	1320 lm/m	1150 lm/m
<b>Qty LED</b>				29 LED/m		
<b>Distance between LED</b>				34,2 mm		
<b>Can be cut into section</b>				24 cm		
<b>Width</b>				10 mm		
<b>Height</b>				3 mm		
<b>Color temperature / Wavelength scope</b>	6500 K	5000 K	3500 K	3000 K	4000 K	2700 K
<b>Beam angle</b>				120°		
<b>Color rendering index (Ra)</b>				80		
<b>Operating temperature</b>				-25 - +60°C		
<b>Storage temperature</b>				-40 - +80°C		
<b>IP degree</b>				IP20		



In spite of all our efforts, we do not guarantee, that technical data doesn't include any mistakes or defects, which can't be basis of any claiming. Figures and pictures are for illustration only and can be different from authentic appearance of product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Bars and Strips](#) category:*

*Click to view products by [Optoflash](#) manufacturer:*

Other Similar products are found below :

[ZLF0310W62524](#) [LF1D-F2F-2W-300](#) [HH-SWW320F210W24-COB IP65](#) [HH-SNW320F210W12-COB IP65](#) [HH-SNW320F010W12-COB IP20](#) [HH-SNW320F210W24-COB IP65](#) [HH-SNW320F010W24-COB IP20](#) [HH-SNW528F210W12-COB IP65](#) [HH-SNW528F010W12-COB IP20](#) [HH-SNW528F010W24-COB IP20](#) [HH-SCW320F210W12-COB IP65](#) [HH-SCW320F010W12-COB IP20](#) [HH-SCW528F210W12-COB IP65](#) [HH-SCW528F010W12-COB IP20](#) [HH-SR528F010W12-COB IP20](#) [HH-SR528F010W24-COB IP20](#) [LF2D-EN2F-2W-A](#) [PUUA-100LLL-NK2P](#) [HC-F12V-3535 PCBA](#) [HC-F12V-WS2811-3535](#) [HC-F24V-6L-36LED-W-WS2821/IP20](#) [HC-F5V-144L-144LED-B-WS2813 IP20](#) [HC-F5V-144L-144LED-B-WS2813 IP65](#) [HC-F5V-144L-144LED-W/IP65](#) [HC-F5V-144L-144LED-W-WS2813 IP20](#) [HC-F5V-30L-30LED-B-WS2813 IP20](#) [HC-F5V-60L-60LED-B-WS2813 IP20](#) [HC-F5V-60L-60LED-W-WS2813 IP65](#) [HC-T12V-10L-30LED-W/IP20](#) [HC-T12V-16L-48LED-W/IP20](#) [HC-T12V-16L-48LED-W/IP65](#) [HC-T12V-20L-60LED-W/IP65](#) [LFBHL-SW860-24V-12D83-20](#) [LFBLL-SW860-24V-5S200-20-IC](#) [LFBML-MW827860-24V-12D83-20](#) [LFBML-SW827-24V-6S167-20](#) [LM-SAG1-W2](#) [LMV-MINI-W2](#) [LS-2835W120RN](#) [LS-2835W120RN1](#) [LS-2835W60RN2](#) [LS-2835WW120R-1](#) [LS-2835WW60RN](#) [LS-3014WW60RN](#) [LS-3014WW60RN3](#) [LS-3528W60RN-1](#) [LS-3528W60RN-2](#) [LS-5050F60R-2](#) [LS-5050F60RN-3](#) [LS-5050W30RN](#)