	TECHNICAL DATASHEET	code	CA00630
		date	2014-01-30
		Version	3
	Cable assembly IP20 RJ45-RJ45 CAT5e 4PR	page	1/2



1. Application:

DataTuff® Patchcord terminated with IP20 RJ45 on both sides for interconnection of data communication equipment such as Industrial Ethernet.

2. Description:

Cable assembly consisting of BELDEN 74002NH: 4PR AWG26/7 CAT5E SF/UTP FRNC with both sides connectorised to a 8 position IP20 Industrial RJ45 CRIMP MALE connector and molded boot.

3. Codenumber:

Belden Codenumbers: CA00630.00Cyy.

The “C” represents the cable is coiled into a ring, a D represents a ring with length <1mtr

The “yy” represents the length of the patchcord.

Example:

CA00630.00C10 = 74002NH IP20 RJ45 - IP20 RJ45 10m

CA00630.00D03 = 74002NH IP20 RJ45 - IP20 RJ45 0.30 m


4. Mechanical and electrical properties:

High voltage test :	1.5kV_dc between contacts and contact to housing
Wire continuity:	tested each wire/contact and shield
Operating temperature rating:	-10 up to +60°C
Storage temperature rating:	-40 up to +70°C

See table 2 for additional mechanical requirements.

Test Title	Agency Standard
Insert Loss/ attenuation	ISO/IEC 11801 or TIA/EIA-568-B.2 Clause 4.5 and 6.0 including 1.2 or greater de-rating factor for stranded cables
FEXT loss	TIA/EIA-568-B.2 clause 6
NEXT(*)	ISO/IEC 11801 A2
Return Loss	ISO/IEC 11801 A2
Coupling attenuation	ISO/IEC 24702 table 4 E ₂ class D channel minimum
Delay	TIA/EIA-568-B.1 de-rated according to length based on 100 meter channel
Delay Skew	TIA/EIA-568-B.1
Note: Next requirement de-rated according ISO/IEC 11801 according to cable length	

Table 1: RJ- 45 Cordset Electrical/Transmission Requirements

	TECHNICAL DATASHEET	code	CA00630
		date	2014-01-30
		Version	3
	Cable assembly IP20 RJ45-RJ45 CAT5e 4PR	page	2/2









Test Title	Test Conditions	Pass Criteria
Installation pull simulation	With connector mated to a jack, apply 20 pound load for 1 minutes to cable in line with axis of connector at room temperature.	<p>Must Pass</p> <p>Electrical/Transmission requirements in chart above before, and after testing.</p> <p>No signs of degradation to cable, connector or cable to connector interface after load removed.</p>

Table 2: RJ45 IDC Industrial cordset Additional Mechanical Requirements

5.1 Connector RJ45 requirements:

Mechanical	IEC 60603-7-4
Electrical/ Transmission	IEC 60603-7-4 and TIA 568B.2
Insertion life	> 750 mating cycles (EIA/TIA-568-B.2 annex K.6.2.2.2)
Contact resistance	20 mΩ maximum
Category	5e minimum

5.2 Wiring scheme: According EIA/TIA 568B

TIA568B	Pin assignment RJ45
Pin no.	Colour of insulation
1	White/Orange 
2	Orange 
3	White/Green 
4	Blue 
5	White/Blue 
6	Green 
7	White/Brown 
8	Brown 

6. Change history:

Revision #	Date	By
1	3-10-2012	PBe
2	24-1-2014	PBe
3	30-1-2014	LC



Belden declares this product to be in compliance with the environmental regulations EU RoHS (Directive 2011/65/EU, 02 Jan. 2013); this is valid for all material produced after the RoHS compliant date for this product.

© Belden Wire & Cable B.V.

All rights are reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)