



HEADERS & RECEPTACLES



TE CONNECTIVITY (TE) 24 MTE HDR SRRA LATCH W/HLDWN [AMPMODU](#) | [AMPMODU MTE](#)

2-103673-3
TE Internal Number: 2-103673-3

Not EU RoHS or ELV Compliant
[Find Compliant Alternatives](#)

Centerline **2.54 mm [.1 in]**

Number of Positions **24**

PCB Mounting Orientation **Right Angle**

PCB Mounting Style **Through Hole**

Number of Rows **1**

✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

Product Drawings

[HDR ASSY, RTANG, SINGLE ROW 2.54\[.100\] C/L 0.641\[.025\] SQ. POST, WITH PLZN & HOLD DOWNS, AMPMODU MTE](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[AMPMODU_MTE_INTERCONNECT_SYSTEM_QRG_4-1773458-0](#)

PDF
English

Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[AMPMODU MTE CONNECTORS](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Right Angle
	Product Type	Connector
	Connector Type	Header
	Strain Relief	Without
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Plug
	PCB Orientation Feature	No
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	24
	Number of Rows	1
	Backwall/Post Interruptions	Without
Electrical Characteristics	Dielectric Withstanding Voltage	600 V
	Insulation Resistance	5000 MΩ
	Termination Resistance	15 MΩ
Body Features	Header Type	Shrouded
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (μ in)	15
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]
	Contact Shape	Square
	Contact Termination Area Plating Material	Tin
	Tail Plating Material	Tin-Lead
	Tail Plating Thickness	2.54 μm [100 μin]
	Contact Type	Pin
	Solder Tail Contact Plating Material	Tin-Lead
	Contact Current Rating (A)	3
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Brass
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	PCB Mounting Style	Through Hole

PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	With
PCB Mount Retention Type	Hold-Down
Contact Retention	With
Mating Alignment Type	Latched
Contact Retention Type	Locking Lance
Mating Retention Type	Hold-Down
Mating Alignment	With

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic

Dimensions	Tail Length	3.3 mm [.13 in]
	Mating Post Length	5.84 mm [.23 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Height	13.59 mm [.535 in]
	Length	63.5 mm [2.5 in]

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
------------------	----------------------------------	------------------

Operation/Application	For Use With	Receptacle Housing Assembly
	Pick and Place Cover	Without

Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476

Packaging Features	Packaging Method	Tube, Tube/Box
	Packaging Quantity	8

Other	Comment	Use Keying Tool No. 91417-1 to remove post for keying.
-------	---------	---

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 1 Results

[View All](#)

Compare 0/10

Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - FFC Connectors
FFC | FFC

024 HOUSING FFC RCPT 100CL SR - 2-487526-3

TE INTERNAL NUMBER: 2-487526-3

Active

Always EU RoHS/ELV Compliant

Connector Type **Housing**

Connector Style **Receptacle**

Centerline **2.54 mm**

Number of Positions **24**

Number of Rows **1**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)