




Ring Terminal, Non-Insulated

- Ring tongue design assures a secure connection in high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Brazed seam protects terminal barrel from splitting during the crimp process

- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Maximum recommended operating temperature 302°F (150°C)
- UL and CSA rated up to 2000 V per UL 486A/B, where applicable



| Part Number | Wire Range | | Stud Size | | Length | | Width | | Clearance | | Panduit Crimping Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|-------------|-----------------|-----------|-----|--------|------|-------|------|-----------|------|--|----------------|----------------|
| | AWG | mm ² | In. | mm | In. | mm | In. | mm | In. | mm | | | |
| P14-8R-C | 18 – 14 AWG | 1.0 – 2.5 | #8 | M4 | 0.71 | 18.0 | 0.31 | 7.9 | 0.25 | 6.4 | CT-100A‡, CT-200‡, CT-600-A‡, CT-1570‡, CT-2500‡ | 100 | 1000 |
| P14-10R-C | | | #10 | M5 | 0.71 | 18.0 | 0.31 | 7.9 | 0.25 | 6.4 | | 100 | 1000 |
| P14-14R-C | | | 1/4" | M6 | 0.91 | 23.1 | 0.46 | 11.7 | 0.38 | 9.7 | | 100 | 1000 |
| P14-56R-C | | | 5/16" | M8 | 0.91 | 23.1 | 0.46 | 11.7 | 0.38 | 9.7 | | 100 | 1000 |
| P14-38R-C | | | 3/8" | M10 | 1.0 | 25.4 | 0.53 | 13.5 | 0.43 | 10.9 | | 50 | 500 |
| P14-12R-L | 14 – 10 AWG | 2.5 – 6.0 | 1/2" | M12 | 1.20 | 30.5 | 0.72 | 18.3 | 0.53 | 13.5 | CT-100A‡, CT-200‡, CT-600-A‡, CT-1570‡, CT-1701‡, CT-2500‡ | 50 | 500 |
| P10-8R-L | | | #8 | M4 | 0.78 | 19.8 | 0.31 | 7.9 | 0.31 | 7.9 | | 50 | 500 |
| P10-10R-L | | | #10 | M5 | 0.81 | 20.6 | 0.38 | 9.7 | 0.31 | 7.9 | | 50 | 500 |
| P10-14R-L | | | 1/4" | M6 | 0.96 | 24.4 | 0.52 | 13.2 | 0.38 | 9.7 | | 50 | 500 |
| P10-56R-L | | | 5/16" | M8 | 0.96 | 24.4 | 0.52 | 13.2 | 0.38 | 9.7 | | 50 | 500 |
| P10-38R-L | 8 AWG | 10.0 | 3/8" | M10 | 1.05 | 26.7 | 0.58 | 14.7 | 0.44 | 11.2 | CT-1701‡, CT-2600 with Die Insert CD-2600-8‡ | 50 | 500 |
| P10-12R-L | | | 1/2" | M12 | 1.20 | 30.5 | 0.72 | 18.3 | 0.53 | 13.5 | | 25 | 250 |
| P8-10R-Q | | | #10 | M5 | 1.14 | 29.0 | 0.47 | 11.9 | 0.43 | 10.9 | | 25 | 250 |
| P8-14R-Q | | | 1/4" | M6 | 1.14 | 29.0 | 0.47 | 11.9 | 0.43 | 10.9 | | 25 | 250 |
| P8-56R-Q | | | 5/16" | M8 | 1.25 | 31.8 | 0.59 | 15.0 | 0.51 | 13.0 | | 25 | 250 |
| P8-38R-Q | 6 AWG | 16.0 | 3/8" | M10 | 1.25 | 31.8 | 0.59 | 15.0 | 0.51 | 13.0 | CT-1701‡, CT-2600 with Die Insert CD-2600-6‡ | 25 | 250 |
| P8-12R-Q | | | 1/2" | M12 | 1.36 | 34.5 | 0.82 | 20.8 | 0.54 | 13.7 | | 20 | 200 |
| P6-10R-E | | | #10 | M5 | 1.21 | 30.7 | 0.47 | 11.9 | 0.43 | 10.9 | | 20 | 200 |
| P6-14R-E | | | 1/4" | M6 | 1.21 | 30.7 | 0.47 | 11.9 | 0.43 | 10.9 | | 20 | 200 |
| P6-56R-E | | | 5/16" | M8 | 1.33 | 33.8 | 0.62 | 15.7 | 0.51 | 13.0 | | 20 | 200 |
| P6-38R-E | 4 AWG | 25.0 | 3/8" | M10 | 1.33 | 33.8 | 0.62 | 15.7 | 0.51 | 13.0 | CT-1701‡, CT-2600 with Die Insert CD-2600-4‡ | 20 | 200 |
| P6-12R-E | | | 1/2" | M12 | 1.43 | 36.3 | 0.82 | 20.8 | 0.51 | 13.0 | | 20 | 200 |
| P4-14R-E | | | 1/4" | M6 | 1.40 | 35.6 | 0.55 | 14.0 | 0.50 | 12.7 | | 20 | 200 |
| P4-56R-E | | | 5/16" | M8 | 1.46 | 37.1 | 0.68 | 17.3 | 0.50 | 12.7 | | 20 | 200 |
| P4-38R-E | | | 3/8" | M10 | 1.46 | 37.1 | 0.68 | 17.3 | 0.50 | 12.7 | | 20 | 200 |
| P4-12R-E | 2 AWG | 35.0 | 1/2" | M12 | 1.55 | 39.4 | 0.86 | 21.8 | 0.53 | 13.5 | CT-1701‡, CT-2600 with Die Insert CD-2600-4‡ | 20 | 200 |
| P2-14R-X | | | 1/4" | M6 | 1.46 | 37.1 | 0.68 | 17.3 | 0.58 | 14.7 | | 10 | 100 |
| P2-56R-X | | | 5/16" | M8 | 1.46 | 37.1 | 0.68 | 17.3 | 0.58 | 14.7 | | 10 | 100 |
| P2-38R-X | | | 3/8" | M10 | 1.46 | 37.1 | 0.68 | 17.3 | 0.58 | 14.7 | | 10 | 100 |
| P2-12R-X | | | 1/2" | M12 | 1.55 | 39.4 | 0.86 | 21.8 | 0.58 | 14.7 | | 10 | 100 |

‡UL and CSA approved tooling/product combinations.
 For crimping tool information, see page M.46 of SA-NCCB51.
 For the full selection of Panduit Crimping Tools see www.panduit.com.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#) [751-250](#)