


# (55 SERIES) PA1

CALUS



Rating
6A 125V AC 3A 250V AC
Contact resistance
50mΩ Max
Insulation resistant
DC 500V 100MΩ Min
Dielectric strength
AC 1000V 1 minute
Cut out



4 mm max

## FEATURES

- \* MATERIAL: Phenolic base (UL flame: 94V-0).  
Contacts and Terminals are copper with silver alloy and silver plated.
- \* Epoxy sealed for dust and moisture resistant.

## PA1

FUNCTION	BUTTON	TERMINAL
0 1  OFF 2P SPST ON	A 	1  SO 2  PC 3  PC Angle(2.54) 5  PC Angle(3.8)
0 2  ON 3P SPDT ON		
0 6  ON 3P SPDT ON		

# **X-ON Electronics**

Authorized  
Distributor

*Click to view  
similar products  
for [Pushbutton](#)*

Switches *category*:

XB6CA61B

P4323221

P7631222

XACA960

8121SDWGE

A22LDWT11M

9001BGC214 921

1301260028

12412806164

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [SCI manufacturer](#):*

Other Similar products are found below :

[LW1L-M1C10V-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M7E-HRN2](#) [67021K512](#) [67081K512X](#) [701PB580](#) [719-5504-000](#)  
[MDPSSGLFS](#) [810KSV30B](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8646AB6X718UL](#) [8646ABUL](#) [FSDWH](#) [9001KXRK](#)  
[9001T8BK](#) [9533CD4+U574+U4922](#) [1203MRA](#) [A22EM01S](#) [A595](#) [1202A6](#) [12037A2ULCSA](#) [1203A2UL](#) [ABD122N-B](#) [1211390004](#)  
[ABN111-Y](#) [1211500044](#) [1211580012](#) [1212MRA](#) [1232A6NF](#) [RA3CSH6A](#) [1241.1183.7047](#) [1241.2511](#) [1241.3428](#) [1223A2ULCSA](#)  
[1223MRA](#) [1232AX2119](#) [1241.1183.8000](#) [1241.1183.8029](#) [1241.2506](#) [1241.2606](#) [12MA6](#) [1301940184](#) [RELBARF6X10\(PLASTIC\)](#)  
[13435AG](#) [13440AD2G25X822+U4546](#) [13445A4GX768](#)