



Approval	 	
Capability		
Standard	UL	IEC
Rated Voltage	600V	800V
Rated Current	30A	32A
Wire size	24-10AWG	0.2-4.0mm ²
T/W/End plate	6.2/42.5/1.6mm	
Height(mm)(NS35:7.5/NS35:15/NS32)	47/54.5/52mm	
Rated surge voltage/Contamination Class	8KV/3	
Stripping length	8mm	
Screw thread/Tightening torque	M3/0.5N.m/4.5Lb-in	
Internal cylindrical gage	A4	
Insulating Material/Inflammability class	PA/V-0	
Specification	Model	Pieces
(1) Terminal block	PC 4	50
(2) End cover	D-PC 2.5	200
(3) Fixed bridge	FBI 2-6 FBI 3-6 FBI 5-6 FBI 10-6	150 100 50 25
(4) Step bracket		
(5) Insertion bridge	EB 2-6 EB 3-6 EB 10-6	100 100 50
(6) Isolator bridge bar, 10P	ISSBI 10-6	10
(7) Bridge bar isolator	IS-K4	100
(8) Switching bridge	USBR 2-7	1
(9) Separating plate	TS-K	1000
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket	DSB 3/10/4	100
(12) Test plug socket insulated	DSBJ 3/13/4	100
(13) Zack strip	ZB6	250


HOW TO ORDER :

- **P** - -

X	X	X
Customer Request		

Series No. No. of pole Color

1	Gray	4	Green	7	Transp-arent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	White

 mm (INCH)	 DEGSON ELECTRONICS CO., LTD.
 THREANGLE PROJECTION	NAME PC 4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIN Rail Terminal Blocks](#) category:

Click to view products by [Degson](#) manufacturer:

Other Similar products are found below :

[1045932](#) [00110420202](#) [00110430402](#) [5724.2/L](#) [592808-3](#) [CTS25U/BL](#) [CTS2.5U-N/Y](#) [90.080](#) [91.010](#) [91.040](#) [DP25-GY-ND](#) [15288](#) [90.070](#)
[90.202](#) [90.905](#) [91.001](#) [91.020](#) [91.201](#) [91.340](#) [2713793](#) [280-331](#) [283-317](#) [283-607](#) [2909044](#) [2909798](#) [29-2052](#) [SRT2-OD08CL-1](#)
[CDL4U\(E\)MOV](#) [2757801](#) [2794660](#) [284-317](#) [2890975](#) [2907033](#) [3048496](#) [CTS2.5U-N/O](#) [5542152](#) [5602077](#) [0709880](#) [5520682](#) [5607102](#)
[EPUSC](#) [SRT2-OD16P](#) [2901288](#) [591620-2](#) [1-591651-1](#) [NRA37-1/2](#) [592814-1](#) [592814-3](#) [SRT2-ID16P](#) [NRA37-12](#)