



NOTE:
MATERIAL: NAN YA 1403G3,PBT WITH 15%GF,UL 94V-0

SPECIFICATION MODEL: KS-101

△ RATING: 15A 250VAC (UL/ CUL)
10A 250VAC (VDE/CCC/SEM/KO/
DEM/KO/FIM/KO/NEM/KO)
INSULATION RESISTANCE: 100M Ω, DC 500V
DIELECTRIC STRENGTH: 2000VAC FOR 1 MINUTE
MEET UL 498 & IEC/EN60320 REQUIREMENTS

REVISION	DESCRIPTION	REVISED BY	TOLERANCES	ANGLE	UNIT	PART NAME	DWG NO
△2005.09.27	增加安規,重新出圖.	孫斌	.X±0.1	±	mm	KS-101 規格圖 B-277	S0298D
△2005.08.22	標示端子孔尺寸	唐雙軍	.XX ±0.05				
△2005.01.03	修改RATING內容.	余龍					
△2004.04.21	更換圖框,首次出圖	梁春林					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC Power Entry Modules](#) category:

Click to view products by [Canal manufacturer](#):

Other Similar products are found below :

[0098.0050](#) [6-1609987-9](#) [6167.0002](#) [7-6609955-2](#) [FN389-4-22](#) [FN9233ER-12-06](#) [FN9233S1-10-06](#) [FN9233S1-8-06](#) [FN9233S1B-8-06](#)
[FN9233S1R-1-06](#) [FN9233S1R-12-06](#) [FN9233SB-1-06](#) [FN9233SB-12-06](#) [FN9233SB-8-06](#) [FN9233SR-10-06](#) [FN9233SR-3-06](#) [FN9244B-15-06](#)
[HI](#) [FN9244EB-3-06](#) [FN9244EB-8-06](#) [FN9244ER-15-06](#) [FN9244ER-8-06](#) [FN9244ES1-8-06](#) [FN9244ESB-8-06](#) [FN9244EU-6-06](#)
[FN9244R-12-06](#) [FN9244R-3-07](#) [FN9244R-8-06](#) [FN9244S1-10-06](#) [FN9244S1-12-06](#) [FN9244S1-3-06](#) [FN9244S1B-6-06](#) [FN9244S1R-3-06](#)
[FN9244S-6-06](#) [FN9244SB-10-06](#) [FN9244SB-6-06](#) [FN9244SB-8-06](#) [FN9244SR-10-06](#) [FN9244SR-6-06](#) [FN9244U-3-06](#) [FN9244U-8-06](#)
[FN9260A-6-06](#) [PE00SSSXB](#) [Fuse-H-EUR-1](#) [Fuse-H-USA-1](#) [PM00XD000](#) [PS0SSDBX0](#) [PS0SXSH3B](#) [A-0701-HT-H](#) [RAPC3FG](#) [15EJMS8](#)