

### ◆FEATURES

1. Small size and large capacitance, high ripple current.
2. Temperature cycle: 1000 cycles.
3. X7R temperature characteristics.
4. Excellent noise absorption.
5. For reflow soldering use.
6. Suitable for aluminum substrate.


### ◆APPLICATIONS

1. Smoothing circuit of switching mode AC-DC or DC-DC converter.
2. On-board power supply.
3. Noise suppressor for various kinds of equipments.

### ◆CUSTOM MADE PRODUCTS

We can offer custom made one element metal cap type capacitors for request of customers.  
Please contact us if you have questions for details.

### ◆CONSTRUCTION



### ◆RATINGS

1. Category Temperature Range	-55~+125℃
2. Rated Voltage Range	25, 50, 100, 250V <sub>dc</sub>
3. Rated Capacitance Range	1.5 to 47μF
4. Rated Capacitance Tolerance	M(±20%)
5. Temperature Characteristics	X7R
6. Rated Ripple Current	See No.5 on the following table

### ◆SPECIFICATIONS

No.	Items	Specification	Test Condition						
1	Withstand Voltage	No abnormality.	250% of rated voltage shall be applied for 5 seconds. (Only 250V <sub>dc</sub> products : 475V)						
2	Insulation Resistance	100/C <sub>R</sub> (MΩ) or 4000(MΩ) whichever is less.	Rated voltage shall be applied for 60±5 seconds at temperature 25±2℃.						
3	Rated Capacitance	Within specified tolerance.		C <sub>R</sub> ≤10μF	C <sub>R</sub> >10μF				
			Temperature	25±2℃					
4	Dissipation Factor	5.0% maximum	Frequency	1±0.1kHz	120±12Hz				
			Voltage	1±0.2Vrms	0.5±0.2Vrms				
5	Rated Ripple Current	<table><tr><td>Size</td><td>55</td></tr><tr><td>Arms</td><td>3.0</td></tr></table>	Size	55	Arms	3.0	10kHz~1MHz (sine curve) Ripple voltage V <sub>p</sub> shall be less than the rated voltage.		
Size	55								
Arms	3.0								


### ◆SPECIFICATIONS

No.	Items	Specification	Test Condition															
6	Temperature Cycle	Appearance : No visible damage. ΔC/C : ±15% D.F. : To meet the initial specification. I.R. : To meet the initial specification.	<table><tr><td>Step</td><td>Temperature (°C)</td><td>(min.)</td></tr><tr><td>1</td><td>Min. Category temperature ±3</td><td>30±3</td></tr><tr><td>2</td><td>Room temperature</td><td>3 max.</td></tr><tr><td>3</td><td>Max. Category temperature ±3</td><td>30±3</td></tr><tr><td>4</td><td>Room temperature</td><td>3 max.</td></tr></table>	Step	Temperature (°C)	(min.)	1	Min. Category temperature ±3	30±3	2	Room temperature	3 max.	3	Max. Category temperature ±3	30±3	4	Room temperature	3 max.
			Step	Temperature (°C)	(min.)													
			1	Min. Category temperature ±3	30±3													
			2	Room temperature	3 max.													
			3	Max. Category temperature ±3	30±3													
			4	Room temperature	3 max.													
<Cycle> 1000 cycles																		
7	Humidity Load Life	Appearance : No abnormality. ΔC/C : ±20% D.F. : 10% max. I.R. : 25/C <sub>R</sub> (MΩ) or 1000(MΩ) whichever is less.	Temperature : 40±2℃															
			Humidity : 90 to 95%RH															
			Voltage : Rated voltage															
8	Endurance	Appearance : No abnormality. ΔC/C : ±20% D.F. : 10% max. I.R. : 50/C <sub>R</sub> (MΩ) or 1000(MΩ) whichever is less.	Time : 500± <sup>24</sup> <sub>0</sub> hours															
			Temperature : 125±3℃															
			Voltage : Rated voltage															
Time : 1000± <sup>48</sup> <sub>0</sub> hours																		

\* $C_R$  : Rated Capacitance( $\mu\text{F}$ )

### ◆Note of mountig for NTJ series.


1. The gap of capacitor and a substrate shall be the mounting face.
2. To prevent degradation of temperature cycling capability, if need to be careful about amount of solder that would not go into the inner side of terminations.




## ◆STANDARD RATINGS

Rated voltage (Vdc)	Rated Capacitance (μF)	Dimensions(mm)				Maximum ripple current (Arms)	Part Number
		L	W	Tmax.	a		
25	33	6.0±0.4	5.3±0.4	5.5	1.3±0.3	3.0	KTJ250B336M55BFT00
	47						KTJ250B476M55BFT00
50	15	6.0±0.4	5.3±0.4	5.5	1.3±0.3	3.0	KTJ500B156M55BFT00
	22						KTJ500B226M55BFT00
100	6.8	6.0±0.4	5.3±0.4	5.5	1.3±0.3	3.0	KTJ101B685M55BFT00
	10						KTJ101B106M55BFT00
250	1.5	6.0±0.4	5.3±0.4	5.5	1.3±0.3	3.0	KTJ251B155M55BFT00
	2.2						KTJ251B225M55BFT00

## ◆PART NUMBERING SYSTEM



## ◆DIMENSIONS



Please refer to "Part Numbering System" of the beginning of a catalog for the details.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Multilayer Ceramic Capacitors MLCC - SMD/SMT](#) *category:*

*Click to view products by* [United Chemicon](#) *manufacturer:*

Other Similar products are found below :

[M39014/01-1467](#) [M39014/02-1218V](#) [M39014/02-1225V](#) [M39014/02-1262V](#) [M39014/02-1301](#) [M39014/22-0631](#) [1210J5000102JCT](#)  
[1210J2K00102KXT](#) [1210J5000103KXT](#) [1210J5000223KXT](#) [D55342E07B379BR-TR](#) [D55342E07B523DR-T/R](#) [1812J1K00103KXT](#)  
[1812J1K00473KXT](#) [1812J2K00680JCT](#) [1812J4K00102MXT](#) [1812J5000102JCT](#) [1812J5000103JCT](#) [1812J5000682JCT](#) [NIN-FB391JTRF](#)  
[NIN-FC2R7JTRF](#) [NPIS27H102MTRF](#) [C1206C101J1GAC](#) [C1608C0G1E472JT000N](#) [C2012C0G2A472J](#) [2220J2K00101JCT](#)  
[KHC201E225M76N0T00](#) [LRC-LRF1206LF-01R025FTR1K](#) [1812J1K00222JCT](#) [1812J2K00102KXT](#) [1812J2K00222KXT](#)  
[1812J2K00472KXT](#) [2-1622820-7-CUT-TAPE](#) [2220J3K00102KXT](#) [2225J2500824KXT](#) [CCR07CG103KM](#) [CGA2B2C0G1H010C](#)  
[CGA2B2C0G1H040C](#) [CGA2B2C0G1H050C](#) [CGA2B2C0G1H060D](#) [CGA2B2C0G1H070D](#) [CGA2B2C0G1H151J](#) [CGA2B2C0G1H1R5C](#)  
[CGA2B2C0G1H2R2C](#) [CGA2B2C0G1H3R3C](#) [CGA2B2C0G1H680J](#) [CGA2B2C0G1H6R8D](#) [CGA2B2X8R1H221K](#) [CGA2B2X8R1H472K](#)  
[CGA3E1X7R1C474K](#)