

This document was generated on 02/01/2016

# PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0930713001

Status: **Active** 

RAST 2.5 Connector System **Overview:** 

5.00mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 5 Circuits, Reference K00, Glow **Description:** 

Wire Compatible

**Documents:** 

3D Model Packaging Specification PK-93070-001 (PDF) **Drawing (PDF)** RoHS Certificate of Compliance (PDF)

Product Specification PS-93070-001 (PDF)

## **Agency Certification**

LR19980 **CSA** UL E29179

General

**PCB Headers Product Family** 

Series 93071

Application Power, Wire-to-Board

Comments "This Molex product is manufactured from material

that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options."


RAST 2.5 Connector System

**Product Name** RAST 2.5 **UPC** 883906320867

**Physical** 

Overview

Breakaway No Circuits (Loaded) 5 Circuits (maximum) 5 Color - Resin Natural Durability (mating cycles max) 10 First Mate / Last Break No Flammability 94V-0 Glow-Wire Compliant Yes Guide to Mating Part No Keving to Mating Part Yes Lock to Mating Part Yes Material - Metal Brass Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon



Series image - Reference only

## **EU ELV**

**Not Relevant** 

**EU RoHS China RoHS** 

Compliant

**REACH SVHC** 

Contains SVHC(2014 December 17): No

**Halogen-Free** 

**Status** 

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS **ELV** 

Green Image Not Relevant

## Search Parts in this Series

93071 Series

### **Mates With**

Appli-Mate RAST 2.5 Female Connector 93051, Appli-Mate RAST 2.5 IDT Housing 91717, Appli-Mate® RAST Power IDT Housing 91627

### **Use With**

**RAST Standard Interface** 

Net Weight 2.020/g Number of Rows Orientation Vertical **PCB** Locator Yes **PCB** Retention None PCB Thickness - Recommended 1.50mm Packaging Type Carton Pitch - Mating Interface 5.00mm Plating min - Mating 3.048µm Plating min - Termination 3.048µm Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No

Temperature Range - Operating -20C to +120C
Termination Interface: Style Through Hole

**Electrical** 

Current - Maximum per Contact 6.0A Voltage - Maximum 250V

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-93070-001
Product Specification PS-93070-001
Sales Drawing SD-93071-001

This document was generated on 02/01/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

1424439 1424438 09330062652 2-8675P1 580129-2 605601-1 6340G1 6341G1 6360G1 6373G1 6374g2 6396G1 647757-1 66394-4
6643411-1 6646058-2 6646137-1 6646138-1 6646348-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1
6651778-1 6651788-1 696465-1 696475-1 73000005059 73000005349 73000005642 73080255059 73080965046 765-15-0080A
765-16-0080B 789.700-44 789.700-54 80-1010 80-9 827381-1 829992-1 902-77-02113 PL00U-301-10D10 PM103MOOLOO
PM16S1620S32-50 PM212MOOLOO PM309FOOLOO PM324FOOLCH