

Art No. CV0037B

Mini DisplayPort 1.2 to DVI Converter Active Type

The CV0037B & CV0058B, are a new generation DisplayPort[™] to DVI[™] converter that receives both video and audio streams from an upstream DisplayPort Source link and converts to a DVI output.

This CV0037B is a Mini DisplayPort 1.2 to DVI signal format converter for interfacing new generation DisplayPort[™] based PC and notebook computers with high definition displays. The Mini DisplayPort to DVI Adapter seamlessly connect next generation DisplayPort based MacBook, MacBook Pro, or MacBook Air with a Mini DisplayPort to conventional DVI displays, such as CRT, LCD monitors and projectors. Mini DisplayPort offers a unified, scalable, and cost effective interface for embedded and external display applications. As desktop and notebook PCs are increasingly transitioning from conventional analog type interfaces to DisplayPort, the converter facilitates the transition by offering seamless connectivity between new DisplayPort PC and the installed base DVI monitors and projectors.

It offers solutions for digital entertainment center, HDTV retail and show site, HDTV, STB, DVD and Projector factory, noise space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

Feartures:

- Integrates a complete DisplayPort receiver and complete DVI transmitter for video format conversion
- Fully compliant DisplayPort 1.2 input, and DVI output
- DVI 1.0 transmitter support
- Supports HDCP1.3 content protection
- Supports DVI highest video resolution 1920 X 1080@60Hz
- Supports multiple color format: RGB 6/8/10/12 bpc (bit per component), YCbCr 4:4:4, and YCbCr 4:2:2 8/10/12 bpc

RoHS

- Supports 10/12-bit deep color 1080p up to 2.25Gbps
- Content protection of HDCP Rx and Tx keys to support HDCP repeater
- Powered from Mini DisplayPort port source
- Displayport active adapter supports Multi Stream Transport (MST)





Art No. CV0037B

Mini DisplayPort 1.2 to DVI Converter Active Type

Specification:

Signal Input/Output	
Input Video Signal	Mini DisplayPort
Maximum Single Link Range	1920x1080@60Hz
Output Video	DVI
Input Connector	Mini DisplayPort Male 20pin
Output Connector	DVI Female (24+1)
Operating Frequency	
Vertical Frequency Range	50/60Hz
Video Amplifier Bandwidth	1.62Gbps/2.7Gbps
Resolutions (HDTV)	
No 3D Mode	Up to 1920x1080@60Hz
3D Mode	Non-support
Mechanical	
Weight (Net)	14g
Product dimension	175 x 43 x 15mm
Cable length	15cm
Environmental	
Operating Temperature	0 °C to +70 °C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10 °C to +80 °C
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	
External Power Supply	No external power needed
Power consumption (Max)	1W




RoHS compliant

* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.



Art No. CV0037B

Mini DisplayPort 1.2 to DVI Converter Active Type



DVI



RoHS CE

Package Contents:

- 1x Mini DisplayPort 1.2 to DVI adapter
- 1x User manual

Packaging Information:

- Packing Dimension: 162 x 230 x 2mm
- Packing Weight: 0.04kg
- Carton Dimension: 570 x 420 x 260mm
- Carton Q'ty: 90pcs
- Carton Weight: 6.2kg



* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI Cables category:

Click to view products by Logilink manufacturer:

Other Similar products are found below :

 426301400-3
 cab-DP to HDMI Passive
 HD2003 010S1
 68783-0055
 PND400
 UA0329
 50472
 50586
 HD0003
 HD0102
 31888
 31889

 31893
 31897
 31907
 31908
 31911
 31913
 31914
 31915
 31919
 31920
 31921
 31923
 31926
 31929
 31935
 31936
 31937
 31941

 31943
 31944
 CV0036B
 CV0038
 CV0057
 CV0057B
 CV0058B
 CV0059B
 50580
 50581
 50582
 50989
 50992
 51579

 51586
 51724
 51758