

TECHNICAL DATA

Scapa 2547

EPR Self-Amalgamating Tape

DESCRIPTION

Scapa 2547 is an insulating, self-amalgamating tape based on EPR (Ethylene Propylene Rubber). Its colour is black.

APPLICATIONS

- For jointing and repairing power cables up to 69 kV.
- For insulation, waterproofing and protection of electrical connections (e.g. satellite 'dish').
- For binding and sealing for the continuity of the lead sheath.

PRODUCT BENEFITS

- Excellent physical and electrical properties with a high degree of stability under conditions of use.
- The tape amalgamates rapidly when applied under tension to provide a void-free homogeneous wrapping, without the need for external heat or pressure.
- Excellent resistance to water, UV and ozone.
- The tape will remove cleanly when cut, allowing it to be used as temporary insulation or protection.
- The product is approved to EDF HN 26-S-04.
- Meets specification UTE C 33-011.
- Service temperature -40 to +100°C. Overload temperature 120°C.
- Supplied in an easy to handle and apply tape form. The product is interleaved with a disposable plastic liner.

Issue: 5 Date: 19/02/03 Page 1 of 2 2547.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Thickness	mm	0.75	
Tensile Strength	MPa	3	BS 903
Elongation at Break	%	800	BS 903
Volume Resistivity	Ohm.m	1 x 10 ¹³	ASTM D257
Dielectric Loss Angle	-	0.004	ASTM D150
Dielectric Strength	kV/mm	44	ASTM D149

STANDARD PRESENTATION

Roll length: 3m, 5m, 7m, 9.1m, 10m

■ Roll width: 19mm, 25mm

Core: 38mm dense plastic

Packaging: Individually shrink-wrapped rolls

Branding: Scapa

RECOMMENDATIONS

Care should be taken to avoid direct contact between the tape and petroleum-type solvents and oils. Oils may affect the electrical properties of the tape.

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

lssue: 5 Date: 19/02/03 Page 2 of 2 2547.doc

www.scapa.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by Scapa manufacturer:

Other Similar products are found below:

PF24.0W 4718 4516-1/4x36 56-YELLOW-34"X72YD 00-021200-13972-7 021200-64630 60 TAPE (1") 62-GRAY-12"X36YD 62-GRAY-12"X36YD 69-1"X36YD 764-1"x36yd-Red 764-1"x36yd-White PG ASSY 926-1/4X18YD 967454-1 1194-14"X36YD 1181 19MM X 16,5 METERS 1182-7.7X10 1245-34"X18YD 1267 130C-1X15FT 130-1x10FT 1345-3/8x18yrd 1380-2"X8" E39-RS1-CA 1900-48mm 22-1/2X36YD 2229-P-2-1/2x3-3/4 88-SUPER-34X44FT 890103N001 2670 SJ3527N-Black-1.5"x50yd EVK-TA-TM047NBH01 AD-UCUSB-DCAUD-SPL 20-1"X60YDS 2020-18mmx55m H150 3900-Blue 3939-24mmx55m 396-1"x36yd 4016-34"x36yd 4462W-12"x72yd 44-TAN-14"X90YD 4504-34x18 471-Trans-1"x36yd-Bulk 5414 34X36 C-22 35-Gray-1/2 371-Tan-48mmx50m 4008-12"X36YD