

TECHNICAL DATA

Scapa 2702

PVC Electrical Adhesive Tape

DESCRIPTION

Scapa 2702 is a 0.13mm premium quality, electrical self-extinguishing soft PVC tape which uses an aggressive pressure sensitive rubber-based adhesive system. It has been designed for use where a recognised specification or international standard is required and where environmental safety is a concern.

APPLICATIONS

- Used for electrical cables wrapping in automotive application
- Hand application
- Primary electrical insulation
- Protection for low and medium voltage cable splices
- Colour coding

PRODUCT BENEFITS

- Good resistance to abrasion, corrosion and moisture
- High dielectric strength and good mechanical protection
- Outstanding conformability
- Environmentally friendly technology
- Approved by IMQ, VDE, ÖVE
- Conforms to BS3924
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)
- Service temperature: -40°C to +105°C

Issue: 4 Date: 25/01/2005 Page 1 of 2 2702.doc

www.scapa.com

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Thickness	mm	0.13	CEI EN 60454
Tensile Strength	N/cm	25	CEI EN 60454
Elongation at Break	%	180	CEI EN 60454
Adhesion to Steel	N/cm	1.8	CEI EN 60454
Adhesion to Backing	N/cm	1.8	CEI EN 60454
Dielectric Strength	KV/mm	40	CEI EN 60454
Flammability		Self extinguishing	CEI EN 60454

STANDARD PRESENTATION

Roll length : 10, 20, 25 and 33 metres
Roll width : 12, 15, 19 and 25mm

■ Core : 32 mm Scapa branded cardboard core

Packaging : Cellowrapped with Scapa label and bar code

Colours : Black, Blue, Brown, Green, Grey, Red, Yellow, Yellow/Green and White

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°c and +25°c. Use within 24 months of receipt.

The tape should be applied with sufficient tension to ensure an optimum bonding and a minimum of two layers with a half overlap. The final layer should be wrapped with a lower tension to prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Issue: 4 Date: 25/01/2005 Page 2 of 2 2702.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in the products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by Scapa manufacturer:

Other Similar products are found below:

PF24.0W 4718 4516-1/4x36 56-YELLOW-34"X72YD 00-021200-13972-7 021200-64630 60 TAPE (1") 62-GRAY-12"X36YD 62-GRAY-12"X36YD 69-1"X36YD 764-1"x36yd-Red 764-1"x36yd-White PG ASSY 926-1/4X18YD 967454-1 1194-14"X36YD 1181 19MM X 16,5 METERS 1182-7.7X10 1245-34"X18YD 1267 130C-1X15FT 130-1x10FT 1345-3/8x18yrd 1380-2"X8" E39-RS1-CA 1900-48mm 22-1/2X36YD 2229-P-2-1/2x3-3/4 88-SUPER-34X44FT 890103N001 2670 SJ3527N-Black-1.5"x50yd EVK-TA-TM047NBH01 AD-UCUSB-DCAUD-SPL 20-1"X60YDS 2020-18mmx55m H150 3900-Blue 3939-24mmx55m 396-1"x36yd 4016-34"x36yd 4462W-12"x72yd 44-TAN-14"X90YD 4504-34x18 471-Trans-1"x36yd-Bulk 5414 34X36 C-22 35-Gray-1/2 371-Tan-48mmx50m 4008-12"X36YD