



PRODUCT DATASHEET

CO₂/Humidity/Temperature Datalogger

Records data on an SD card in Excel® format

For easy transfer to a PC for analysis



Features:

- Checks for Carbon Dioxide (CO₂) concentrations
- Maintenance free dual wavelength NDIR (non-dispersive infrared) CO₂ sensor
- Triple LCD simultaneously displays CO₂, Temperature and Relative Humidity
- Measurement ranges:

CO₂: 0 to 4,000ppm

Temperature: 32 to 122°F (0 to 50°C)

Humidity: 10 to 90%RH

- Datalogger date/time stamps and stores readings on an SD card in Excel® format for easy transfer to a PC
- Selectable data sampling rate: 5, 10, 30, 60, 120, 300, 600 seconds or Auto
- Complete with (6) AAA batteries, 2G SD memory card, Universal AC adaptor, and mounting bracket





Specifications	
CO ₂	0 to 4,000ppm
Accuracy	±40ppm (<1000ppm); ±5% rdg (>1000ppm)
Resolution	1ppm
Temperature	32 to 122°F (0 to 50°C)
Accuracy	±1.8°F/0.8°C
Resolution	0.1°F/°C
Humidity	10 to 90%
Accuracy	±4%RH
Resolution	0.1%
Datalogging	2,000K data using 2G SD memory card
Dimensions	5.2 x 3.1 x 1.3" (132 x 80 x 32mm)
Weight	9.9oz (282g)

Ordering Information:

 $\textbf{SD800}......CO_{2} / \text{Humidity/Temperature Datalogger}$



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160