



### Construction



### Wiring Method



1. dimensions As shown
2. Insulation resistance:  $\geq 100$  up to 500V=
3. dielectric strength  
2 KV 50Hz 2 sec.
4. TESTING: 100% OPEN AND SHORT AND MISWIRE TEST.
5. 100% RoHS COMPLIANT.

No	Item	Length	Packaging
67347	BQFWG 0150	1.5m	1/10/80/180
67348	BQFWG 0250	2.5m	1/10/80/120
67349	BQFWG 0350	3.5m	1/10/40/80
67350	BQFWG 0500	5.0m	1/10/30/80
67351	BQFWG 0750	7.5m	1/5/20/40
67352	BQFWG 1000	10m	1/5/20/40

6	MOULDER	PVC 48P White	15g
5	CONNECTOR S2	F QUICK 90° Plug (Nickel plating 100% Shielded )	1set
4	Copper coil	φ4.5mm H8mm	2PCS
3	MOULDER	PVC 48P White	12g
2	CABLE	φ5.3 RG88 COAXIAL CABLE White(According to the chart)	L
1	CONNECTOR S1	F QUICK Plug (Nickel plating 100% Shielded )	1set
NO	Item Name	SPEC	QTY
Edition	WEC/000	Scale	
Designed by	ming hong	Item Name	F QUICK PLUG TO F QUICK 90° PLUG COAXIAL CABLE
Checked by		Item NO	<b>BQFWG series cable</b>
Approved by		Unit: MM	
Date	11.28.2013		



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Specialised Cables](#) category:*

*Click to view products by [Goobay](#) manufacturer:*

Other Similar products are found below :

[GP-IE515546DS-002](#) [96CB-L2020PIB2](#) [1200740161](#) [R88ACAKA0015SRE](#) [R88ACAWL005SDE](#) [1300660042](#) [1300660201](#) [1971465-2](#)  
[22733-8](#) [2R7004A20F060](#) [SSL009PC2DC012N](#) [FC2A-KC6C](#) [CCSFCBF2](#) [R7ACAB005S](#) [XS2WM12PUR4SA10M](#)  
[XS2WM12PVC4SA10M](#) [05AU05](#) [UCABLE](#) [10114734-2010LF](#) [XW2Z010H3](#) [XW2Z010H1](#) [5-1589827-8](#) [5-1589827-4](#) [861084-1](#)  
[XW2Z200JB24](#) [5-1589956-8](#) [CR4000A76M020](#) [1201140211](#) [1300140039](#) [CR4000A76M005](#) [CR4006A76M005](#) [10077488-N0550FDLF](#)  
[XW2ZRY150C](#) [I4JPBJLUXX100](#) [I4JPBJLUXX50](#) [CM06](#) [CM06W](#) [POE004](#) [0243 009 05](#) [0243 009 20](#) [0243 009 36](#) [0243 009 26](#) [0243 009](#)  
[23](#) [0243 009 01](#) [0243 009 30](#) [0243 008 05](#) [0243 008 20](#) [0243 008 36](#) [0243 008 23](#) [0243 008 01](#)