

SEI-110-02-GF-S-E-TR

SEI-120-02-GF-S

SIBF-10-F-S-AD

SIBF-25-F-S-AD

SIBF-05-F-S-AD

(1,00 mm) .0394" (SEI) (1,27 mm) .050" (SIBF)

SEI, SIBF SERIES

ONE PIECE INTERFACE

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?SEI

Insulator Material: Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating: Au over 50µ" (1,27 µm) Ni
Current Rating: 2.3 A per pin (1 pin powered)
Operating Temp Range: -55°C to +125°C
Mating Force: 50g (0,49 N) per contact
Voltage Rating: 400 VAC
Cycles: 100 min
Contact Deflection: (0,46 mm) .018" nominal
RoHS Compliant: Yes

Processing:
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,10 mm) .004" max (05-25)
 (0,15 mm) .006" max (30)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



SEI	1	NO. OF POSITIONS	02	PLATING OPTION	S	INSERT OPTION	ALIGNMENT OPTION	OTHER OPTION	
		05, 10, 15, 20, 25, 30 (Standard sizes)			-G = 10µ" (0,25 µm) Gold -GF = 3µ" (0,08 µm) Gold flash	Leave blank for Short Version (No screw down inserts or holes) -E = #2-56 x 1/16" screw thread -M = 2,00 mm x 0,40 mm screw thread	Leave blank for no Alignment Pin -AT = Alignment Pin Top Side -AB = Alignment Pin Bottom Side	-TR = Tape & Reel	

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?SIBF

Insulator Material: Black Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating: Au or Sn over 50µ" (1,27 µm) Ni
Current Rating: 2.5 A per pin (1 pin powered)
Operating Temp Range: -55°C to +125°C
Voltage Rating: 155 VAC
RoHS Compliant: Yes

Processing:
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,10 mm) .004" max (05-20)
 (0,15 mm) .006" max (25)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



SIBF	NO. OF POSITIONS	PLATING OPTION	S	OPTION
		-05, -10, -20, -25	-F = Flash Gold, Matte Tin on tail	-AD = Top & Bottom Alignment Pin

SIBF 3 mm Stack Height	Rated @ 3dB Insertion Loss*
Single-Ended Signaling	7 GHz / 14 Gbps
Differential Pair Signaling	7.5 GHz / 15 Gbps

*Test board losses de-embedded from performance data.
 Performance data for other stack heights and complete test data available at www.samtec.com?SIBF or contact sig@samtec.com

ALSO AVAILABLE (MOQ Required)

- Additional positions
- Top or bottom side only alignment pin

Contact Samtec.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)