



MOISTURE SEALED LITEPIPE® ASSEMBLY

SPECIFICATIONS

MATERIAL	LITEPIPE® - Acrylic (Clear optical grade) CLIPLITE® Lens - Polycarbonate, Seal - J-Von Retaining Ring - Polypropylene (black) (U.L. Listed Materials)
DESIGN	Low profile lens assembly with moisture seal and LITEPIPE®.
MOUNTING	Mounts in .281" (7.2mm) hole on 3/8" centers. Panel thickness 1/32" to 1/8". Compression of the seal is accomplished by pressing the retaining ring into place.
STANDOFF	Use standoff to adjust height of standard LED above the PCB in order to maintain a maximum .050" clearance between LITEPIPE® and LED. See STD Series data sheet on page 28.



VERSATILITY

The LITEPIPE® assembly provides a method of transmitting the light from PCB mounted LEDs to the front display panel while providing moisture protection. Both styles of LEDs, surface mount, 3mm and 5mm standard packages can be displayed in this manner.

LITEPIPE® increases the apparent brightness and viewing angle of a PCB mounted LED. LITEPIPE® transmits the light from the source to the lens, which in turn disperses the light up to 180 degrees.


APPLICATION

The LITEPIPE® assembly meets NEMA 3 conditions for moisture and dust. Because there is no physical connection between the lightpipe and PCB mounted LED, the circuit board can be installed or removed without disturbing the panel display.

INSTALLATION


The LITEPIPE® and CLIPLITE® lens assembly is easily installed. Pass assembly through the panel opening and press on retaining ring to secure unit to the panel. Slide PCB into position aligning LED with the end of the LITEPIPE® unit.

APPLICATION




Pass lens through panel opening. Press on retaining ring. Air gap .050″ maximum between LED and LITEPIPE $^{\$}$. Use standoff to adjust LED height.

PANEL ASSEMBLY



Hold lens tightly to panel, careful not to mar lens surface. Use 5/16" nut driver or deep socket to press on retaining ring, compressing seal.

ORDERING CODES



OUTLINE DRAWING RECOMMENDED LEDs LMS LITEPIPE®/Lens Assembly **RNG 268** .130 DIA. MOISTURE SEAL 3mm .36 DIA. .230 DIA. XXX (XX.XXmm) **SEE PAGE 29-31**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Light Pipes category:

Click to view products by Visual Communications manufacturer:

Other Similar products are found below:

1367627-1 SLP3-300-450-F SLP3-400-450-R LPA-C011301S-23 LPA-C011301S-6 LPF-C011306S 515-1061-803F 515-1142-170F 5151155F VLP-640-F LMC-034-CTP LPA-C011301S-5.4 LPA-C041301S-2 LPA-S011331S LPC_155_CTP LPC_182_CTP LPC_190_CTP
515-1001-802F 515-1027-803F 515-1048-801F 515-1142-195F 515-1146F 515-1148F 515-1217F SLP3-150-300-R SLP3-500-450-R 5151058F 515-1064-810F 515-1114-801F FLPR-SBC FLPV-SG FLPR-SG BDL-1187 7511A41 7511A62V0 7511F2 FLPV-SBC SLP3-300250-R 5151064802F LPF-R011340S 515-1166-801F FLPF-6.0 SLP3-350-200-F LC-11.25 CLP-1214 1296.2044 515-1064-808F FLX3_05
515-1192-0025-0DF 515-1192-80-3DF