


Switchmode/High Frequency Common Mode Inductors

ET3542-057

Description:

Common-mode coils are useful in a wide range of applications for the prevention of electromagnetic interference (EMI) and radio frequency interference (RFI) from power supply lines and for prevention of malfunctioning of various electronic equipments. Features include low leakage flux, high self-resonant frequency, high impedance at applicable frequency and low stray capacitance in section winding. Designed to meet UL, CSA and IEC standards.



Electrical Specifications (@20°C):

| Min. | Inductance | Max. DC (Ω) | Amps |
|-------------|------------|-------------|------|
| Inductance* | Difference | Resistance | RMS |
| (mH) | (µH) Max | | |
| 4.70 | 150 | .080 | 4.00 |

*inductance per winding.

Specifications:

Rated Voltage = 250VAC Temperature Rise = 45° C Max Insulation Resistance = $100M \Omega$ Min Operating Temperature Range = -20 to 105° C Dielectric Withstanding Voltage = 2,000 VAC


Dimensions:

| W | L | Н | А | В | |
|------------------|-------|-------|------|------|--|
| 1.496 | 1.024 | 1.772 | .827 | .591 | |
| Linita in inches | | | | | |

Units in inches.


Weight: 2.60 oz.


Schematic:




RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.







PIN MOUNTING

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fixed Inductors category:

Click to view products by Triad manufacturer:

Other Similar products are found below :

MLZ1608M6R8WTD25 MLZ1608N6R8LT000 MLZ1608N3R3LTD25 MLZ1608N3R3LT000 MLZ1608N150LT000 MLZ1608M150WTD25 MLZ1608M3R3WTD25 MLZ1608M3R3WT000 MLZ1608M150WT000 MLZ1608A1R5WT000 MLZ1608N1R5LT000 B82432C1333K000 PCMB053T-1R0MS PCMB053T-1R5MS PCMB104T-1R5MS CR32NP-100KC CR32NP-151KC CR32NP-180KC CR32NP-181KC CR32NP-1R5MC CR32NP-390KC CR32NP-3R9MC CR32NP-680KC CR32NP-820KC CR32NP-8R2MC CR43NP-390KC CR43NP-560KC CR43NP-680KC CR54NP-181KC CR54NP-470LC CR54NP-820KC CR54NP-8R5MC MGDQ4-00004-P MGDU1-00016-P MHL1ECTTP18NJ MHL1JCTTD12NJ PE-51506NL PE-53601NL PE-53630NL PE-53824SNLT PE-62892NL PE-92100NL PG0434.801NLT PG0936.113NLT PM06-2N7 PM06-39NJ HC2LP-R47-R HC2-R47-R HC3-2R2-R HC8-1R2-R