

RSMC


Konfektionierbarer Steckverbinder, M8-Stecker mit Schraubverschluss, Konfektionierung über Lötanschlüsse

Field attachable connector, M8 male connector with threaded joint, assembling with solder connections


RSMCW

Konfektionierbarer Steckverbinder, M8-Winkelstecker mit Schraubverschluss, Konfektionierung über Lötanschlüsse

Field attachable connector, M8 male right angle connector with threaded joint, assembling with solder connections



*a O-Ring
O-ring



*a Kabelverschraubung
Screw joint for cable

Pinbelegung
Pin assignment

3-polig
3 poles





4-polig
4 poles



Technische Daten	
Umgebungstemperatur	RSMC: -25°C / +80°C RSMCW: -40°C / +85°C
Werkstoffe	
Gehäuse / Griffkörper	RSMC: CuZn, vernickelt RSMCW: PBT
Kontaktträger	PA
Kontakt	RSMC: CuZn, unternickelt und 0,8 µm vergoldet RSMCW: CuZn, vergoldet
Gewindebuchse / Rändel- schraube/-mutter / Sechskant- schraube/-mutter / Hülse	RSMC: CuZn, vernickelt RSMCW: CuZn
Mechanische Daten	
Schutzart	IP 67 Nur im verschraubten Zustand mit den dazugehörigen Gegen- stücken.
Anschlussart Anschließer Leiter	Lötanschluss RSMC: max. 0,34 mm ² RSMCW: max. 0,25 mm ²
Elektrische Daten	
Durchgangswiderstand	≤ 5 mΩ
Nennstrom bei 40°C	4 A
Nennspannung	3-polig 60 V 4-polig 30 V
Bemessungsspannung	3-polig 63 V 4-polig 36 V
Prüfspannung	RSMC: 3-polig 1,5 kV eff. / 60 s 4-polig 0,8 kV eff. / 60 s RSMCW: 0,9 kV eff. / 60 s
Isolationswiderstand	> 10 ⁹ Ω
Verschmutzungsgrad	3

Technical data	
Operating temperature range	RSMC: -25°C / +80°C RSMCW: -40°C / +85°C
Materials	
Housing / Molded body	RSMC: CuZn, nickel-plated RSMCW: PBT
Insert	PA
Contact	RSMC: CuZn, pre-nickel and 0.8 microns gold-plated RSMCW: CuZn, gold-plated
Receptacle shell / knurled screw/ nut / hexagon screw/nut / sleeve	RSMC: CuZn, nickel-plated RSMCW: CuZn
Mechanical data	
Degree of protection	IP 67 Only in locked position with its proper counterparts.
Mode of connection	solder connection
Connectable conductor	RSMC: max. 0.34 mm ² RSMCW: max. 0.25 mm ²
Electrical data	
Contact resistance	≤ 5 mΩ
Nominal current at 40°C	4 A
Nominal voltage	3 poles 60 V 4 poles 30 V
Rated voltage	3 poles 63 V 4 poles 36 V
Test voltage	RSMC: 3 poles 1.5 kV eff. / 60 s 4 poles 0.8 kV eff. / 60 s RSMCW: 0.9 kV eff. / 60 s
Insulation resistance	> 10 ⁹ Ω
Pollution degree	3

Bestellbezeichnung Designation		Polzahl Poles	Kabelverschraubung Screw joint for cable	
RSMC 3	RSMCW 3	3	Ø 3,5–5,0 mm	
RSMC 4	RSMCW 4	4	Ø 3,5–5,0 mm	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular MIL Spec Connector](#) category:

Click to view products by [Lumberg](#) manufacturer:

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)