



Adhesive-Lined Polyolefin Tubing

φ3.2 x 76mm (black)	18 pcs	φ3.2 x 76mm (red)	18 pcs
φ4.8 x 76mm (black)	10 pcs	φ4.8 x 76mm (red)	10 pcs
φ6.4 x 76mm (black)	6 pcs	φ6.4 x 76mm (red)	6 pcs
φ9.5 x 76mm (black)	3 pcs	φ9.5 x 76mm (red)	3 pcs
φ12.7 x 76mm (black)	2 pcs	φ12.7 x 76mm (red)	2 pcs
φ19.1 x 76mm (black)	1 pcs	φ19.1 x 76mm (red)	1 pcs



Material: Polyethylene
 Operating Temperature: -45°C ~ +125°C
 Shrink Temperature: Start at 70°C; Shrunk Totally at 120°C
 Shrink Ratio: 3:1
 Maximum Electrical Rating: 600 Volts

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Fix & Fasten](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [611112-000](#) [617867N001](#) [6500750004](#) [CZ1420-000](#) [D-306-38](#) [770-003S106W2](#) [770-005S105W1](#) [770-005S106W1](#) [770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MFT-MT2000-NO.14-0-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#)