

Aluminum Electrolytic Capacitors Axial Standard




Fig. 1

| QUICK REFERENCE DATA | |
|--|------------------------|
| DESCRIPTION | VALUE |
| Nominal case sizes (Ø D x L in mm) | 4.5 x 10 to 10 x 25 |
| Rated capacitance range, C _R | 1 µF to 1000 µF |
| Tolerance on C _R | -10 % to +50 % |
| Rated voltage, U _R | 6.3 V to 100 V |
| Category temperature range | -40 °C to +85 °C |
| Endurance test at 85 °C | 2000 h |
| Useful life at 85 °C | 3000 h |
| Useful life at 40 °C, 1.4 x I _R applied | 80 000 h |
| Shelf life at 0 V, 85 °C | 500 h |
| Based on sectional specification | IEC 60384-4 / EN130300 |
| Climatic category IEC 60068 | 40 / 085 / 56 |

FEATURES

- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Axial leads, cylindrical aluminum case, insulated with a blue sleeve
- Taped version available for automatic insertion
- Charge and discharge proof
- Useful life: 3000 h at 85 °C
- Standard dimensions
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


**RoHS
COMPLIANT**

APPLICATIONS


- General purpose and industrial, automotive, telecommunication, audio-video
- Coupling, decoupling, timing, smoothing, filtering, buffering in SMPS
- Boards with restricted mounting height, vibration, and shock resistant

MARKING

The capacitors are marked (where possible) with the following information:


- Rated capacitance (in µF)
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (T for -10 % to +50 %)
- Rated voltage (in V)
- Date code in accordance with IEC 60062
- Code factory of origin
- Name of manufacturer
- Negative terminal identification
- Series number (030 or 031)

| SELECTION CHART FOR C_R , U_R AND RELEVANT NOMINAL CASE SIZES ($\varnothing D \times L$ in mm) | | | | | | | |
|---|-----------|----------|----------|----------|----------|----------|----------|
| C_R (μF) | U_R (V) | | | | | | |
| | 6.3 | 10 | 16 | 25 | 40 | 63 | 100 |
| 1.0 | - | - | - | - | - | 4.5 x 10 | 4.5 x 10 |
| 2.2 | - | - | - | - | - | 4.5 x 10 | 4.5 x 10 |
| 3.3 | - | - | - | - | - | 4.5 x 10 | 4.5 x 10 |
| 4.7 | - | - | - | - | - | 4.5 x 10 | 6 x 10 |
| 6.8 | - | - | - | - | - | 4.5 x 10 | 6 x 10 |
| 10 | - | - | - | 4.5 x 10 | 4.5 x 10 | 6 x 10 | 8 x 11 |
| | - | - | - | - | - | - | 6.5 x 18 |
| 15 | - | - | - | - | 4.5 x 10 | 6 x 10 | - |
| 22 | - | - | - | 4.5 x 10 | 6 x 10 | 8 x 11 | 8 x 18 |
| | - | - | - | - | - | 6.5 x 18 | - |
| 33 | - | - | 4.5 x 10 | - | 6 x 10 | - | 10 x 18 |
| 47 | - | 4.5 x 10 | - | 6 x 10 | 8 x 11 | 8 x 18 | 10 x 25 |
| | - | - | - | - | 6.5 x 18 | - | - |
| 68 | 4.5 x 10 | - | 6 x 10 | - | - | 10 x 18 | - |
| 100 | - | 6 x 10 | - | 8 x 11 | 8 x 18 | 10 x 25 | - |
| | - | - | - | 6.5 x 18 | - | - | - |
| 150 | 6 x 10 | - | 8 x 11 | 8 x 18 | 10 x 18 | - | - |
| | - | - | 6.5 x 18 | - | - | - | - |
| 220 | - | 8 x 11 | 8 x 18 | 10 x 18 | 10 x 25 | - | - |
| | - | 6.5 x 18 | - | - | - | - | - |
| 330 | - | 8 x 18 | 10 x 18 | 10 x 25 | - | - | - |
| 470 | 8 x 18 | 10 x 18 | 10 x 25 | - | - | - | - |
| 680 | 10 x 18 | 10 x 25 | - | - | - | - | - |
| 1000 | 10 x 25 | - | - | - | - | - | - |

DIMENSIONS in millimeters AND AVAILABLE FORMS


Form BR: Taped on reel
Form BA: Taped in box (ammopack)
 Case $\varnothing D \times L = 4.5 \text{ mm} \times 10 \text{ mm}$ to $8 \text{ mm} \times 11 \text{ mm}$

Fig. 2 - Forms BA and BR



Form BR: Taped on reel
 Case $\varnothing D \times L = 6.5 \text{ mm} \times 18 \text{ mm}$ to $15 \text{ mm} \times 30 \text{ mm}$
Form BA: Taped in box (ammopack)
 Case $\varnothing D \times L = 6.5 \text{ mm} \times 18 \text{ mm}$ to $10 \text{ mm} \times 25 \text{ mm}$

Fig. 3 - Forms BA and BR

Table 1

| AXIAL; DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES | | | | | | | | | |
|---|-----------|----------------------|------------------------|------------|------------|----------|----------------------|---------|--|
| NOMINAL CASE SIZE $\varnothing D \times L$ | CASE CODE | AXIAL FORM BA AND BR | | | | MASS (g) | PACKAGING QUANTITIES | | |
| | | $\varnothing d$ | $\varnothing D_{max.}$ | $L_{max.}$ | $F_{min.}$ | | FORM BA | FORM BR | |
| 4.5 x 10 | 2 | 0.6 | 5.0 | 10.5 | 15 | ≈ 0.5 | 1000 | 3000 | |
| 6 x 10 | 3 | 0.6 | 6.3 | 10.5 | 15 | ≈ 0.7 | 1000 | 1000 | |
| 8 x 11 | 5a | 0.6 | 8.5 | 11.5 | 15 | ≈ 1.1 | 500 | 500 | |
| 6.5 x 18 | 4 | 0.8 | 6.9 | 18.5 | 25 | ≈ 1.3 | 1000 | 1000 | |
| 8 x 18 | 5 | 0.8 | 8.5 | 18.5 | 25 | ≈ 1.7 | 500 | 500 | |
| 10 x 18 | 6 | 0.8 | 10.5 | 18.5 | 25 | ≈ 2.5 | 500 | 500 | |
| 10 x 25 | 7 | 0.8 | 10.5 | 25.0 | 30 | ≈ 3.3 | 500 | 500 | |

Note

- Detailed tape dimensions see section "PACKAGING"



| ELECTRICAL DATA | |
|-----------------|---|
| SYMBOL | DESCRIPTION |
| C_R | Rated capacitance at 100 Hz, tolerance -10 % to +50 % |
| I_R | Rated RMS ripple current at 100 Hz, 85 °C |
| I_{L1} | Max. leakage current after 1 min at U_R |
| I_{L5} | Max. leakage current after 5 min at U_R |
| $\tan \delta$ | Max. dissipation factor at 100 Hz |
| ESR | Equivalent series resistance at 100 Hz (calculated from $\tan \delta_{max}$ and C_R) |
| Z | Max. impedance at 10 kHz |

ORDERING EXAMPLE

Electrolytic capacitor 031 series

330 μF / 10 V; -10 % / +50 %

Nominal case size: \varnothing 8 mm x 18 mm; form BA

Ordering code: MAL203134331E3

Note

- Unless otherwise specified, all electrical values in Table 2 apply at $T_{amb} = 20\text{ °C}$, $P = 86\text{ kPa}$ to 106 kPa , $RH = 45\%$ to 75% .

Table 2

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | | | | | | |
|--|--------------------------------------|--|--------------|----------------------------------|--|--|-------------------------|-------------------------------|-----------------------------|-----------------------------|-------------------------|
| U_R (V) | C_R 100 Hz (μF) | NOMINAL CASE SIZE $\varnothing D \times L$ (mm) | CASE CODE | I_R 100 Hz 85 °C (mA) | I_{L1} 1 min (μA) | I_{L5} 5 min (μA) | $\tan \delta$ 100 Hz | ESR 100 Hz (Ω) | Z 10 kHz (Ω) | ORDERING CODE MAL2..... | |
| | | | | | | | | | | TAPED ON REEL FORM BR | TAPED IN BOX FORM BA |
| 6.3 | 68 | 4.5 x 10 | 2 | 75 | 22 | 5.9 | 0.25 | 5.86 | 2.90 | 03023689E3 | 03033689E3 |
| | 150 | 6 x 10 | 3 | 120 | 10 | 6.9 | 0.25 | 2.66 | 1.30 | 03023151E3 | 03033151E3 |
| | 470 | 8 x 18 | 5 | 330 | 22 | 11 | 0.25 | 0.85 | 0.43 | 03123471E3 | 03133471E3 |
| | 680 | 10 x 18 | 6 | 430 | 30 | 14 | 0.25 | 0.59 | 0.29 | 03123681E3 | 03133681E3 |
| | 1000 | 10 x 25 | 7 | 560 | 42 | 18 | 0.25 | 0.40 | 0.20 | 03123102E3 | 03133102E3 |
| 10 | 47 | 4.5 x 10 | 2 | 70 | 24 | 5.9 | 0.20 | 6.78 | 3.40 | 03024479E3 | 03034479E3 |
| | 100 | 6 x 10 | 3 | 110 | 10 | 7.0 | 0.20 | 3.19 | 1.60 | 03024101E3 | 03034101E3 |
| | 220 | 8 x 11 | 5a | 210 | 18 | 9.4 | 0.20 | 1.45 | 0.73 | 03024221E3 | 03034221E3 |
| | 220 | 6.5 x 18 | 4 | 210 | 18 | 9.4 | 0.20 | 1.45 | 0.73 | 03124221E3 | 03134221E3 |
| | 330 | 8 x 18 | 5 | 310 | 24 | 12 | 0.20 | 0.97 | 0.48 | 03124331E3 | 03134331E3 |
| | 470 | 10 x 18 | 6 | 410 | 33 | 14 | 0.20 | 0.68 | 0.34 | 03124471E3 | 03134471E3 |
| | 680 | 10 x 25 | 7 | 510 | 45 | 19 | 0.20 | 0.47 | 0.24 | 03124681E3 | 03134681E3 |
| 16 | 33 | 4.5 x 10 | 2 | 65 | 27 | 6.1 | 0.16 | 7.72 | 3.60 | 03025339E3 | 03035339E3 |
| | 68 | 6 x 10 | 3 | 110 | 11 | 7.2 | 0.16 | 3.75 | 1.80 | 03025689E3 | 03035689E3 |
| | 150 | 8 x 11 | 5a | 200 | 19 | 9.8 | 0.16 | 1.70 | 0.80 | 03025151E3 | 03035151E3 |
| | 150 | 6.5 x 18 | 4 | 200 | 19 | 9.8 | 0.16 | 1.70 | 0.80 | 03125151E3 | 03135151E3 |
| | 220 | 8 x 18 | 5 | 270 | 26 | 12 | 0.16 | 1.16 | 0.55 | 03125221E3 | 03135221E3 |
| | 330 | 10 x 18 | 6 | 410 | 36 | 16 | 0.16 | 0.78 | 0.36 | 03125331E3 | 03135331E3 |
| | 470 | 10 x 25 | 7 | 480 | 49 | 20 | 0.16 | 0.55 | 0.26 | 03125471E3 | 03135471E3 |
| 25 | 10 | 4.5 x 10 | 2 | 50 | 13 | 5.5 | 0.14 | 22.3 | 9.00 | 03026109E3 | 03036109E3 |
| | 22 | 4.5 x 10 | 2 | 60 | 28 | 6.1 | 0.14 | 10.2 | 4.10 | 03026229E3 | 03036229E3 |
| | 47 | 6 x 10 | 3 | 100 | 12 | 7.4 | 0.14 | 4.80 | 1.90 | 03026479E3 | 03036479E3 |
| | 100 | 8 x 11 | 5a | 160 | 19 | 10 | 0.14 | 2.23 | 0.90 | 03026101E3 | 03036101E3 |
| | 100 | 6.5 x 18 | 4 | 160 | 19 | 10 | 0.14 | 2.23 | 0.90 | 03126101E3 | 03136101E3 |
| | 150 | 8 x 18 | 5 | 240 | 27 | 13 | 0.14 | 1.49 | 0.60 | 03126151E3 | 03136151E3 |
| | 220 | 10 x 18 | 6 | 350 | 37 | 16 | 0.14 | 1.02 | 0.41 | 03126221E3 | 03136221E3 |
| 330 | 10 x 25 | 7 | 460 | 54 | 22 | 0.14 | 0.68 | 0.27 | 03126331E3 | 03136331E3 | |



| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | | | | | | |
|--|----------------------------------|---|--------------|---|----------------------------------|----------------------------------|-----------------|----------------------|--------------------|-----------------------------|-------------------------|
| U _R (V) | C _R 100 Hz (μF) | NOMINAL CASE SIZE Ø D x L (mm) | CASE CODE | I _R 100 Hz 85 °C (mA) | I _{L1} 1 min (μA) | I _{L5} 5 min (μA) | tan δ 100 Hz | ESR 100 Hz (Ω) | Z 10 kHz (Ω) | ORDERING CODE MAL2..... | |
| | | | | | | | | | | TAPED ON REEL FORM BR | TAPED IN BOX FORM BA |
| 40 | 10 | 4.5 x 10 | 2 | 50 | 20 | 5.8 | 0.11 | 17.6 | 7.00 | 03027109E3 | 03037109E3 |
| | 15 | 4.5 x 10 | 2 | 55 | 30 | 6.2 | 0.11 | 11.7 | 4.70 | 03027159E3 | 03037159E3 |
| | 22 | 6 x 10 | 3 | 75 | 9 | 6.8 | 0.11 | 8.00 | 3.20 | 03027229E3 | 03037229E3 |
| | 33 | 6 x 10 | 3 | 95 | 12 | 7.7 | 0.11 | 5.31 | 2.10 | 03027339E3 | 03037339E3 |
| | 47 | 8 x 11 | 5a | 150 | 16 | 8.8 | 0.11 | 3.73 | 1.50 | 03027479E3 | 03037479E3 |
| | 47 | 6.5 x 18 | 4 | 150 | 16 | 8.8 | 0.11 | 3.73 | 1.50 | 03127479E3 | 03137479E3 |
| | 100 | 8 x 18 | 5 | 220 | 28 | 13 | 0.11 | 1.75 | 0.70 | 03127101E3 | 03137101E3 |
| | 150 | 10 x 18 | 6 | 300 | 40 | 17 | 0.11 | 1.17 | 0.47 | 03127151E3 | 03137151E3 |
| | 220 | 10 x 25 | 7 | 430 | 57 | 23 | 0.11 | 0.80 | 0.32 | 03127221E3 | 03137221E3 |
| 63 | 1.0 | 4.5 x 10 | 2 | 13 | 5 | 5.1 | 0.09 | 143 | 55.0 | 03028108E3 | 03038108E3 |
| | 2.2 | 4.5 x 10 | 2 | 25 | 7 | 5.3 | 0.09 | 65.2 | 25.0 | 03028228E3 | 03038228E3 |
| | 3.3 | 4.5 x 10 | 2 | 35 | 11 | 5.4 | 0.09 | 46.5 | 17.0 | 03028338E3 | 03038338E3 |
| | 4.7 | 4.5 x 10 | 2 | 40 | 15 | 5.6 | 0.09 | 30.5 | 12.0 | 03028478E3 | 03038478E3 |
| | 6.8 | 4.5 x 10 | 2 | 46 | 22 | 5.9 | 0.09 | 21.1 | 8.10 | 03028688E3 | 03038688E3 |
| | 10 | 6 x 10 | 3 | 70 | 7 | 6.3 | 0.08 | 12.8 | 5.50 | 03028109E3 | 03038109E3 |
| | 15 | 6 x 10 | 3 | 79 | 10 | 6.9 | 0.08 | 8.50 | 3.70 | 03028159E3 | 03038159E3 |
| | 22 | 8 x 11 | 5a | 110 | 13 | 7.8 | 0.08 | 5.79 | 2.50 | 03028229E3 | 03038229E3 |
| | 22 | 6.5 x 18 | 4 | 110 | 13 | 7.8 | 0.08 | 5.79 | 2.50 | 03128229E3 | 03138229E3 |
| | 47 | 8 x 18 | 5 | 190 | 22 | 11 | 0.08 | 2.71 | 1.20 | 03128479E3 | 03138479E3 |
| | 68 | 10 x 18 | 6 | 250 | 30 | 14 | 0.08 | 1.88 | 0.81 | 03128689E3 | 03138689E3 |
| 100 | 10 x 25 | 7 | 300 | 42 | 18 | 0.08 | 1.28 | 0.55 | 03128101E3 | 03138101E3 | |
| 100 | 1.0 | 4.5 x 10 | 2 | 20 | 5 | 4.6 | 0.08 | 128 | 45.0 | 03029108E3 | 03039108E3 |
| | 2.2 | 4.5 x 10 | 2 | 30 | 11 | 5.3 | 0.08 | 57.9 | 21.0 | 03029228E3 | 03039228E3 |
| | 3.3 | 4.5 x 10 | 2 | 40 | 17 | 6.0 | 0.08 | 38.6 | 14.0 | 03029338E3 | 03039338E3 |
| | 4.7 | 6 x 10 | 3 | 50 | 13 | 6.8 | 0.07 | 23.7 | 9.60 | 03029478E3 | 03039478E3 |
| | 6.8 | 6 x 10 | 3 | 70 | 18 | 8.0 | 0.07 | 16.4 | 6.60 | 03029688E3 | 03039688E3 |
| | 10 | 8 x 11 | 5a | 90 | 24 | 10 | 0.07 | 11.2 | 4.50 | 03029109E3 | 03039109E3 |
| | 10 | 6.5 x 18 | 4 | 90 | 24 | 10 | 0.07 | 11.2 | 4.50 | 03129109E3 | 03139109E3 |
| | 22 | 8 x 18 | 5 | 120 | 48 | 18 | 0.07 | 5.07 | 2.10 | 03129229E3 | 03139229E3 |
| | 33 | 10 x 18 | 6 | 200 | 70 | 24 | 0.07 | 3.38 | 1.40 | 03129339E3 | 03139339E3 |
| | 47 | 10 x 25 | 7 | 260 | 98 | 33 | 0.07 | 2.37 | 0.96 | 03129479E3 | 03139479E3 |

| ADDITIONAL ELECTRICAL DATA | | |
|------------------------------------|---|---|
| PARAMETER | CONDITIONS | VALUE |
| Voltage | | |
| Surge voltage | | $U_s \leq 1.15 \times U_R$ |
| Reverse voltage | | $U_{rev} \leq 1 \text{ V}$ |
| Current | | |
| Leakage current | After 1 min at U_R : Case $\emptyset D \times L = 4.5 \text{ mm} \times 10 \text{ mm}$ Case $\emptyset D \times L = 6 \text{ mm} \times 10 \text{ mm}$ to $10 \text{ mm} \times 25 \text{ mm}$ $U_R = 100 \text{ V}$ | $I_{L1} \leq 0.05 C_R \times U_R$ or $5 \mu\text{A}$, whichever is greater I_{L1} for $CV \leq 1000$: $\leq 0.01 C_R \times U_R$ or $1 \mu\text{A}$, whichever is greater I_{L1} for $CV > 1000$: $\leq 0.006 C_R \times U_R + 4 \mu\text{A}$ $I_{L1} = 0.02 C_R \times U_R + 4 \mu\text{A}$ |
| | After 5 min: $U_R = 6.3 \text{ V}$ to 63 V $U_R = 100 \text{ V}$ | $I_{L5} \leq 0.002 C_R \times U_R + 5 \mu\text{A}$ $I_{L5} \leq 0.006 C_R \times U_R + 4 \mu\text{A}$ |
| Inductance | | |
| Equivalent series inductance (ESL) | Case $\emptyset D \times L$ mm: | |
| | 4.5 x 10 | typ. 10 nH |
| | 6 x 10 | typ. 22 nH |
| | 8 x 11 | typ. 85 nH |
| | 6.5 x 18 | typ. 25 nH |
| | 8 x 18 | typ. 40 nH |
| | 10 x 18 | typ. 61 nH |
| 10 x 25 | typ. 38 nH | |
| Resistance | | |
| Equivalent series resistance (ESR) | Calculated from $\tan \delta_{max.}$ and C_R (see table 2) | $ESR = \tan \delta / 2\pi f C_R$ |


CAPACITANCE (C)


Fig. 4 - Typical multiplier of capacitance as a function of ambient temperature



Fig. 5 - Typical multiplier of capacitance as a function of frequency

EQUIVALENT SERIES RESISTANCE (ESR)



Fig. 6 - Typical multiplier of ESR as a function of ambient temperature



Fig. 7 - Typical multiplier of ESR as a function of frequency

IMPEDANCE (Z)

Table 3

| T _{amb} | Z x C _R (Ω x μF) | | | | | | |
|------------------|-----------------------------|--------|--------|--------|-------|-------|-------|
| | 6.3 V | 10 V | 16 V | 25 V | 40 V | 63 V | 100 V |
| +20 °C | ≤ 200 | ≤ 160 | ≤ 120 | ≤ 90 | ≤ 70 | ≤ 55 | ≤ 45 |
| -25 °C | ≤ 1200 | ≤ 750 | ≤ 560 | ≤ 400 | ≤ 300 | ≤ 180 | ≤ 130 |
| -40 °C | ≤ 3200 | ≤ 2000 | ≤ 1500 | ≤ 1100 | ≤ 900 | ≤ 500 | ≤ 350 |




Fig. 8 - Typical impedance as a function of frequency




Fig. 9 - Typical impedance as a function of frequency

RIPPLE CURRENT AND USEFUL LIFE

Table 4

| ENDURANCE TEST DURATION AND USEFUL LIFE | |
|---|--------------------------|
| ENDURANCE AT 85 °C (h) | USEFUL LIFE AT 85 °C (h) |
| 2000 | 3000 |

Note

- Multiplier of useful life code: CCC205



Fig. 10 - Multiplier of useful life as a function of ambient temperature and ripple current load

Table 5

| MULTIPLIER OF RIPPLE CURRENT (I_R) AS A FUNCTION OF FREQUENCY | | | | | | |
|---|----------------|------|------|------|------|----------------|
| U_R (V) | FREQUENCY (Hz) | | | | | |
| | 50 | 100 | 300 | 1000 | 3000 | $\geq 10\ 000$ |
| I_R MULTIPLIER | | | | | | |
| 6.3 | 0.95 | 1.00 | 1.07 | 1.12 | 1.15 | 1.20 |
| 10 | 0.95 | 1.00 | 1.07 | 1.12 | 1.15 | 1.20 |
| 16 | 0.90 | 1.00 | 1.12 | 1.20 | 1.25 | 1.30 |
| 25 | 0.90 | 1.00 | 1.12 | 1.20 | 1.25 | 1.30 |
| 40 | 0.85 | 1.00 | 1.20 | 1.30 | 1.35 | 1.40 |
| 63 | 0.85 | 1.00 | 1.20 | 1.30 | 1.35 | 1.40 |
| 100 | 0.85 | 1.00 | 1.20 | 1.30 | 1.35 | 1.40 |



Table 6

| TEST PROCEDURES AND REQUIREMENTS | | | |
|--|-------------------------------------|---|---|
| TEST | | PROCEDURE (quick reference) | REQUIREMENTS |
| NAME OF TEST | REFERENCE | | |
| Case \varnothing D x L = 4.5 mm x 10 mm to 10 mm x 25 mm | | | |
| Endurance | IEC 384-4 / EN130300 subclause 4.13 | $T_{amb} = 85\text{ }^{\circ}\text{C}$; U_R applied; 2000 h | $U_R \leq 6.3\text{ V}$; $\Delta C/C$: +15 % / -30 % $U_R > 6.3\text{ V}$; $\Delta C/C$: $\pm 15\%$ $\tan \delta \leq 1.3 \times \text{spec. limit}$ $Z \leq 2 \times \text{spec. limit}$ $I_L \leq \text{spec. limit}$ |
| Useful life | CECC 30301 subclause 1.8.1 | $T_{amb} = 85\text{ }^{\circ}\text{C}$; U_R and I_R applied; 3000 h | $U_R \leq 6.3\text{ V}$; $\Delta C/C$: +45 % / -50 % $U_R > 6.3\text{ V}$; $\Delta C/C$: $\pm 45\%$ $\tan \delta \leq 3 \times \text{spec. limit}$ $Z \leq 3 \times \text{spec. limit}$ $I_L \leq \text{spec. limit}$ no short or open circuit total failure percentage: $\leq 1\%$ |
| Shelf life (storage at high temperature) | IEC 384-4 / EN130300 subclause 4.17 | $T_{amb} = 85\text{ }^{\circ}\text{C}$; no voltage applied; 500 h After test: U_R to be applied for 30 min, 24 h to 48 h before measurement | $\Delta C/C$, $\tan \delta$, Z: for requirements see "Endurance test" above $I_L \leq 2 \times \text{spec. limit}$ |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) category:

Click to view products by [Vishay](#) manufacturer:

Other Similar products are found below :

[NRELS102M35V16X16C.140LLF](#) [ESRG160ETC100MD07D](#) [227RZS050M](#) [335CKR250M](#) [476CKH100MSA](#) [477CKR100M](#)
[107CKR010M](#) [107CKH063MSA](#) [RJH-25V222MI9#](#) [RJH-35V221MG5#](#) [B43827A1106M8](#) [RJH-50V221MH6#](#) [EKYA500ELL470MF11D](#)
[B41022A5686M6](#) [ESRG250ELL101MH09D](#) [EKMA160EC3101MF07D](#) [RJB-10V471MG3#](#) [ESMG160ETD221MF11D](#)
[EKZH160ETD152MJ20S](#) [RJH-35V122MJ6#](#) [EGXF630ELL621ML20S](#) [RBD-25V100KE3#N](#) [EKMA350ELL100ME07D](#)
[ESMG160ETD101ME11D](#) [ELXY100ETD102MJ20S](#) [EGXF500ELL561ML15S](#) [EKMG350ETD471MJ16S](#) [35YXA330MEFC10X12.5](#)
[RXW471M1ESA-0815](#) [ELXZ630ELL221MJ25S](#) [ERR1HM1R0D11OT](#) [LPE681M30060FVA](#) [LPL471M22030FVA](#) [HFE221M25030FVA](#)
[LKMD1401H221MF](#) [B41888G6108M000](#) [EKMA160ETD470MF07D](#) [UHW1J102MHD6](#) [EKMG500ETD221MJC5S](#) [LKMK2502W101MF](#)
[LKMD1401H181MF](#) [LKMI2502G820MF](#) [LKMJ2001J122MF](#) [LKML2501C472MF](#) [LKMJ4002C681MF](#) [450MXH330MEFCSN25X45](#)
[450MXK330MA2RFC22X50](#) [63ZLH560MEFCG412.5X30](#) [ELH2DM331O25KT](#) [ELH2DM471P30KT](#)