


Specifications:

- Contact rating: 5A, 250V AC
- Contact resistance: 50mOhm max.
- Insulation resistance: 1000MOhm min. at 500V DC
- Dielectric strength: 2000V RMS (50/60Hz)
- Operating temperature: -40°C to +85°C
- Electrical life: 50 000 cycles
- Operating force: 5N max.
- Switching function: on-mom
- Torque: 5-14N max. applied to nut
- IP class: IP 67 front panel protection
- Resistance to impact: IK 09
- Material: Bushing / button: stainless steel with varnished polished
Contact: gold over silver alloy
Nut: nickel plated brass
Base: PBT

CONTACT CONFIGURATION



Tolerances: 0.00 to 10.00: ±0.20mm 10.01 to 20.00: ±0.25mm 20.01 to 30.00: ±0.30mm			Date	Name	<h1>MAV02B22M3GF</h1>
			02/12	dr	
			knitter-switch		<h2>30 25 36</h2>
Operating temperature	03/12	dr			Page
Modifications	Date	Name			1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[LW1L-M1C10V-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M7E-HRN2](#) [67021K512](#) [67081K512X](#) [701PB580](#) [719-5504-000](#)
[MDPSSGLFS](#) [810KSV30B](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8646AB6X718UL](#) [8646ABUL](#)
[FSDWH](#) [9001KXRK](#) [9001T8BK](#) [9533CD4+U574+U4922](#) [1203MRA](#) [A22EM01S](#) [A595](#) [1202A6](#) [12037A2ULCSA](#) [1203A2UL](#) [ABD122N-](#)
[B](#) [1211390004](#) [ABN111-Y](#) [ABN400-R](#) [1211500044](#) [1211580012](#) [1212MRA](#) [1232A6NF](#) [RA3CSH6A](#) [1241.1183.7047](#) [1241.2511](#)
[1241.3428](#) [1223A2ULCSA](#) [1223MRA](#) [1232AX2119](#) [1241.1183.8000](#) [1241.1183.8029](#) [1241.2506](#) [1241.2606](#) [12MA6](#) [1301940184](#)
[RELBARF6X10\(PLASTIC\)](#) [13435AG](#)