


CONTACT CONFIGURATION



x	LED color
R	red
G	green
Y	yellow
O	orange
B	blue
W	white

y	LED voltage (AC/DC)
6V	6V, 15mA
12V	12V, 15mA
24V	24V, 15mA
36V	36V, 15mA
110V	110V, 5mA
220V	220V, 5mA

Specifications:

Contact rating: 5A, 250V AC
 Contact resistance: 50mOhm max.
 Insulation resistance: 1 000MOhm min. at 500V DC
 Dielectric strength: 2 000V RMS (50/60Hz)
 Operating temperature: -40°C to +85°C
 Electrical life: 50 000 cycles
 Operating force: 4N max.
 Switching function: on - mom
 Torque: 5-14Nm max. applied to nut
 IP class: IP67 protection

Material:
 Bushing / button: stainless steel with varnished polished
 Contact: silver alloy
 Nut: nickel plated brass
 Base: PBT



Tolerances: 0.00 to 30.00: ±0.20mm		Date	Name
30.01 to 80.00: ±0.25mm		09/10	dr
Operating temperature	05/11	dr	
Modifications	Date	Name	

MAV02LB22M3FRxLO-y

knitter-switch

30 21 73

Page

1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[LW1L-M1C10V-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M7E-HRN2](#) [67021K512](#) [67081K512X](#) [701PB580](#) [719-5504-000](#)
[MDPSSGLFS](#) [810KSV30B](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8646AB6X718UL](#) [8646ABUL](#)
[FSDWH](#) [9001KXRK](#) [9001T8BK](#) [9533CD4+U574+U4922](#) [1203MRA](#) [A22EM01S](#) [A595](#) [1202A6](#) [12037A2ULCSA](#) [1203A2UL](#) [ABD122N-](#)
[B](#) [1211390004](#) [ABN111-Y](#) [ABN400-R](#) [1211500044](#) [1211580012](#) [1212MRA](#) [1232A6NF](#) [RA3CSH6A](#) [1241.1183.7047](#) [1241.2511](#)
[1241.3428](#) [1223A2ULCSA](#) [1223MRA](#) [1232AX2119](#) [1241.1183.8000](#) [1241.1183.8029](#) [1241.2506](#) [1241.2606](#) [12MA6](#) [1301940184](#)
[RELBARF6X10\(PLASTIC\)](#) [13435AG](#)