Electronics		Search By: ^{In} Part Number Enter a complete or partial part nu	imber
Products Documentation	Resources My Account Customer Suppo	ort About Us	
<u>ie > Products > By Type > I</u>	Ribbon & Flat Flex Wire Connectors > Product Feature	Selector > Product Details	
oduct Details for FS	SN -11D -10		
	FLEXSTRIP ® Jumpers		Quick Links
No Image Available			Check Pricing &
			Availability
	Product Highlights: 2 1.27 mm Centerline		Search for Tooling Product Feature
	? Nomex Insulation Material		Selector Contact Us About
FSN-11D -10	 Insulation Length = 25.40 mm Pin Arrangement (Left) = D 		This Product
Tyco Part Number: 6 -	 Pin Arrangement (Right) = D 		
1437130 - 2	View all Features		
Superseded			
Superseded Contact Product			
Contact Product			
Contact Product Information Center ocumentation & Addit roduct Drawings:			nformation:
Contact Product Information Center ocumentation & Addit			nformation: ct Line Information
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available	tional Information	 Produ Additional F 	ct Line Information Product Images:
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available	tional Information	 Produ Additional F Produ 	ct Line Information Product Images: ct View
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available atalog Pages/Data Sha ? None Available	tional Information eets:	 Produ Additional F 	ct Line Information Product Images: ct View
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available	tional Information eets:	 ? Produ Additional F ? Produ ? Produ ? Produ Related Pro 	<u>ct Line Information</u> Product Images: <u>ct View</u> <u>ct View</u> ducts:
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available atalog Pages/Data She ? None Available roduct Specifications: ? None Available	tional Information eets:	 Produ Additional F Produ Produ 	<u>ct Line Information</u> Product Images: <u>ct View</u> <u>ct View</u> ducts:
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available atalog Pages/Data Sha ? None Available roduct Specifications:	tional Information eets:	 ? Produ Additional F ? Produ ? Produ ? Produ Related Pro 	<u>ct Line Information</u> Product Images: <u>ct View</u> <u>ct View</u> ducts:
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available atalog Pages/Data She ? None Available roduct Specifications: ? None Available pplication Specification ? None Available	tional Information eets:	 ? Produ Additional F ? Produ ? Produ ? Produ Related Pro 	<u>ct Line Information</u> Product Images: <u>ct View</u> <u>ct View</u> ducts:
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available atalog Pages/Data Sha ? None Available roduct Specifications: ? None Available	tional Information eets:	 ? Produ Additional F ? Produ ? Produ ? Produ Related Pro 	<u>ct Line Information</u> Product Images: <u>ct View</u> <u>ct View</u> ducts:
Contact Product Information Center ocumentation & Addit roduct Drawings: ? None Available atalog Pages/Data Sha ? None Available roduct Specifications: ? None Available pplication Specification ? None Available	tional Information eets:	 ? Produ Additional F ? Produ ? Produ ? Produ Related Pro 	<u>ct Line Information</u> Product Images: <u>ct View</u> <u>ct View</u> ducts:

Product Features (Please use the Product Drawing for all design activity)			
Product Type Features: ? Insulation Material = Nomex ? Number of Conductors = 10	Configuration Related Features: ? <u>Pin Arrangement (Left)</u> = D ? <u>Pin Arrangement (Right)</u> = D		
Mechanical Attachment: ? Impedance (?) = 95	Industry Standards: Provide a compliance = Not ELV/RoHS Provide a compliant		
Electrical Characteristics:	? Lead Free Solder Processes = Not reviewed for		

? Current Rating (Amps.) = 1.6

- ? Voltage Rating (VAC) = 200

Body Related Features:

- ? <u>Centerline (mm [in])</u> = 1.27 [0.050]
- ? Insulation Length (mm [in]) = 25.40 [1.000]

lead free solder process

? Brand = Tyco Electronics

```
Conditions for Usage:

    Operating Temperature (°C [°F]) =
    [-40 - +257]
```

Languages : English | Deutsch | Español | Português (do Brasil) | ??????? | Italiano | ???? (??) | ?? (??) | ??? Country Sites : China | Japan

Other:

© 2006 Tyco Electronics Corporation All Rights Reserved Home | Customer Support | Supplier | Site Map | Privacy Policy | Browser Support

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Cables / Networking Cables category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

0152660053 60302002 73-7797-25 73-8890-10 73-8890-14 73-8891-14 73-8891-25 73-8892-50 73-8894-10 73-8894-3 73-8895-14 73-8896-7 MCJB2-10P6Q7-120 84909-0204 9QA0-111-12-3.00 1200650742 1200700174 1200860368 1200650013 1201080008 1-21919-1 1300500373 1300101844 1300101845 130050-0004 1300500014 1410147 E16A06002M030 E200102-009-S1 MT14-187L 17-103530 NK5EPC18RDY NK5EPC18VLY NK5EPC18YLY NK5EPC1GRY NK5EPC30BLY NK5EPC30VLY NK5EPC30YLY NK5EPC4Y NK5EPC6YLY NK5EPC8BLY NK5EPC9YLY NK6PC30BUY NK6PC30GRY NK6PC30RDY NK6PC30YLY 1969343-6 C501100010 C501106002